

(12) PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. AU 199871200 B2
(10) Patent No. 732141

(54) Title
Hydrocarbon gas processing

(51)⁶ International Patent Classification(s)
C07C 007/00 F25J 003/02

(21) Application No: **199871200** (22) Application Date: **1998.04.14**

(87) WIPO No: **WO98/47839**

(30) Priority Data

(31) Number	(32) Date	(33) Country
60/044569	1997.04.21	US

(43) Publication Date : **1998.11.13**

(43) Publication Journal Date : **1999.01.07**

(44) Accepted Journal Date : **2001.04.12**

(71) Applicant(s)
Elcor Corporation

(72) Inventor(s)
C. L. Rambo; John D. Wilkinson; Hank M. Hudson

(74) Agent/Attorney
DAVIES COLLISON CAVE, 1 Little Collins Street, MELBOURNE VIC 3000

[illegible]

ALF9871200

A1


(43) International Publication Date: 29 October 1998 (29.10.98)

(81) Designated States: AU, BR, CA, GB, MX.

Published

With international search report.

(54) Title: HYDROCARBON GAS PROCESSING



(57) Abstract

A process for the recovery of ethane, ethylene, propane, propylene and heavier hydrocarbon components from a hydrocarbon gas stream is disclosed. The stream is divided into first and second streams, and the second stream is cooled and expanded to a lower pressure and supplied to a contacting device. The first stream is cooled to condense substantially all of it, expanded to the lower pressure, and then used to cool a warmer distillation stream from a distillation column to at least partially condense the distillation stream. At least a portion of the partially condensed distillation stream is directed the contacting device to intimately contact the expanded second stream, the resulting vapors and liquids are separated from the contacting device, and these liquids are supplied to the distillation column. The quantities and temperatures of the feeds to the contacting device and the distillation column are effective to maintain the overhead temperatures of the contacting device and the distillation column at temperatures whereby the major portion of the desired components is recovered.

HYDROCARBON GAS PROCESSING

SPECIFICATION

BACKGROUND OF THE INVENTION

This invention relates to a process for the separation of a gas
5 containing hydrocarbons.

Ethylene, ethane, propylene, propane, and/or heavier hydrocarbons can be recovered from a variety of gases, such as natural gas, refinery gas, and synthetic gas streams obtained from other hydrocarbon materials such as coal, crude oil, naphtha, oil shale, tar sands, and lignite. Natural gas usually has a major proportion of
10 methane and ethane, i.e., methane and ethane together comprise at least 50 mole percent of the gas. The gas also contains relatively lesser amounts of heavier hydrocarbons such as propane, butanes, pentanes and the like, as well as hydrogen, nitrogen, carbon dioxide and other gases.

The present invention is generally concerned with the recovery of
15 ethylene, ethane, propylene, propane, and heavier hydrocarbons from such gas streams. A typical analysis of a gas stream to be processed in accordance with this invention would be, in approximate mole percent, 85.6% methane, 6.9% ethane and other C₂ components, 3.0% propane and other C₃ components, 0.5% iso-butane, 1.2% normal butane, 1.1% pentanes plus, with the balance made up of nitrogen and carbon
20 dioxide. Sulfur containing gases are also sometimes present.

The historically cyclic fluctuations in the prices of both natural gas and its natural gas liquid (NGL) constituents have at times reduced the incremental value of ethane, ethylene, propane, propylene, and heavier components as liquid products. Competition for processing rights has forced plant operators to maximize the
25 processing capacity and recovery efficiency of their existing gas processing plants, as well as to provide the ability to more quickly respond to changing market conditions. Available processes for separating these materials include those based upon cooling

and refrigeration of gas, oil absorption, and refrigerated oil absorption. Additionally, cryogenic processes have become popular because of the availability of economical equipment that produces power while simultaneously expanding and extracting heat from the gas being processed. Depending upon the pressure of the gas source, the richness (ethane, ethylene, and heavier hydrocarbons content) of the gas, and the desired end products, each of these processes or a combination thereof may be employed.

The cryogenic expansion process is now generally preferred for natural gas liquids recovery because it provides maximum simplicity with ease of start up, operating flexibility, good efficiency, safety, and good reliability. U.S. Pat. Nos. 4,157,904, 4,171,964, 4,251,249, 4,278,457, 4,519,824, 4,617,039, 4,687,499, 4,689,063, 4,690,702, 4,854,955, 4,869,740, 4,889,545, 5,275,005, 5,555,748, and 5,568,737, reissue U.S. Pat. No. 33,408, co-pending application no. 08/696,114, and co-pending application no. 08/738,321 describe relevant processes (although the description of the present invention in some cases is based on different processing conditions than those described in the cited U.S. Patents).

In a typical cryogenic expansion recovery process, a feed gas stream under pressure is cooled by heat exchange with other streams of the process and/or external sources of refrigeration such as a propane compression-refrigeration system. As the gas is cooled, liquids may be condensed and collected in one or more separators as high-pressure liquids containing some of the desired C_2+ (or C_3+) components. Depending on the richness of the gas and the amount of liquids formed, the high-pressure liquids may be expanded to a lower pressure and fractionated. The vaporization occurring during expansion of the liquids results in further cooling of the stream. Under some conditions, pre-cooling the high pressure liquids prior to the expansion may be desirable in order to further lower the temperature resulting from the expansion. The expanded stream, comprising a mixture of liquid and vapor, is fractionated in a distillation (demethanizer or deethanizer) column. In the column, the expansion cooled stream(s) is (are) distilled to separate residual methane, nitrogen, and other volatile gases as overhead vapor from the desired C_2 components and heavier hydrocarbon components as bottom liquid product (or to separate residual

methane, C₂ components, nitrogen, and other volatile gases as overhead vapor from the desired C₃ components and heavier hydrocarbon components as bottom liquid product).

If the feed gas is not totally condensed (typically it is not), the vapor remaining from the partial condensation can be split into two or more streams. One portion of the vapor is passed through a work expansion machine or engine, or an expansion valve, to a lower pressure at which additional liquids are condensed as a result of further cooling of the stream. The pressure after expansion is essentially the same as the pressure at which the distillation column is operated. The expanded stream is supplied as a feed to the column in a lower region of an absorption section contained in the distillation column and is contacted with cold liquids to absorb the C₂ (or C₃) components and heavier components from the vapor portion of the expanded stream.

The remaining portion of the vapor is cooled to substantial condensation by heat exchange with other process streams, e.g., the cold residue gas. Some or all of the high-pressure liquid may be combined with this vapor portion prior to cooling. The resulting cooled stream is then expanded through an appropriate expansion device, such as an expansion valve, to a pressure slightly above that at which the demethanizer (or deethanizer) column is operated. During expansion, a portion of the liquid will vaporize, resulting in cooling of the total stream. The flash expanded stream is then directed in heat exchange relation with the overhead distillation stream from the demethanizer (or deethanizer), cooling the distillation stream and condensing at least a portion of it, whereupon the warmed expanded stream is supplied to the middle or lower region of the absorption section in the distillation column. The condensed liquid in the cooled distillation stream is removed, leaving the volatile residue gas containing substantially all of the methane (or substantially all of the methane and C₂ components). The condensed liquid stream is then supplied to the distillation column as a top column feed so that the cold liquids contained in the stream can contact the vapor portions of the expanded stream and the warmed expanded stream in the absorption section of the distillation column.

The purpose of this process is to perform a separation that produces a

residue gas leaving the process which contains substantially all of the methane in the feed gas with essentially none of the C_2 components and heavier hydrocarbon components (or substantially all of the methane and C_2 components in the feed gas with essentially none of the C_3 components and heavier hydrocarbon components), and a bottoms fraction leaving the demethanizer (or deethanizer) which contains substantially all of the C_2 components and heavier hydrocarbon components with essentially no methane or more volatile components (or substantially all of the C_3 components and heavier hydrocarbon components with essentially no methane, C_2 components or more volatile components). The present invention provides a means for modifying an existing processing plant to achieve this separation at substantially lower capital cost by eliminating much of the equipment associated with providing reflux for the absorption section of the demethanizer (or deethanizer) column. The present invention, whether applied in a new facility or as a modification to an existing processing plant, can be quickly and easily adjusted to either recover C_2 components in the bottom liquid product, or to reject C_2 components to the volatile residue gas while recovering nearly all of the C_3 components and heavier hydrocarbons in the bottom liquid product. This processing flexibility allows the plant operator to respond to fluctuations in natural gas and ethane prices by operating the processing plant in the manner that produces the highest product revenues.

In accordance with the present invention, it has been found that C_2 recoveries in excess of 86 percent can be maintained while providing essentially complete rejection of methane to the residue gas stream. In addition, it has been found that C_3 recoveries in excess of 97 percent can be maintained while providing essentially complete rejection of C_2 components to the residue gas stream. The present invention, although applicable at lower pressures and warmer temperatures, is particularly advantageous when processing feed gases at pressures in the range of 600 to 1000 psia or higher under conditions requiring column overhead temperatures of -50°F or colder.

For a better understanding of the present invention, reference is made to the following examples and drawings. Referring to the drawings:

FIG. 1 is a flow diagram of a prior art cryogenic natural gas processing plant;

FIG. 2 is a flow diagram illustrating how the processing plant of FIG. 1 can be adapted to be a cryogenic expansion natural gas processing plant of the prior art according to U.S. Pat. No. 4,854,955;

FIG. 3 is a flow diagram illustrating how the processing plant of FIG. 1 can be adapted to be a natural gas processing plant in accordance with the present invention;

FIG. 4 is a flow diagram illustrating an alternative means of adapting the processing plant of FIG. 1 to be a natural gas processing plant in accordance with the present invention;

FIG. 5 is a flow diagram illustrating an alternative means of adapting the processing plant of FIG. 1 to be a natural gas processing plant in accordance with the present invention; and

FIG. 6 is a flow diagram illustrating an alternative means of application of the present invention to a natural gas stream.

In the following explanation of the above figures, tables are provided summarizing flow rates calculated for representative process conditions. In the tables appearing herein, the values for flow rates (in pound moles per hour) have been rounded to the nearest whole number for convenience. The total stream rates shown in the tables include all nonhydrocarbon components and hence are generally larger than the sum of the stream flow rates for the hydrocarbon components. Temperatures indicated are approximate values rounded to the nearest degree. It should also be noted that the process design calculations performed for the purpose of comparing the processes depicted in the figures are based on the assumption of no heat leak from (or to) the surroundings to (or from) the process. The quality of commercially available insulating materials makes this a very reasonable assumption and one that is typically made by those skilled in the art.

DESCRIPTION OF THE PRIOR ART

FIG. 1 is a flow diagram showing the original design of an existing processing plant using prior art to recover C_3+ components from natural gas. As originally designed, inlet gas enters the plant at 95 °F and 950 psia as stream 31. Had the inlet gas contained a concentration of sulfur compounds which would prevent the product streams from meeting specifications, the sulfur compounds would have been removed by appropriate pretreatment of the feed gas (not illustrated). In addition, the feed stream is dehydrated to prevent hydrate (ice) formation under cryogenic conditions (also not illustrated). Solid desiccant is used for this purpose in the existing facility.

The feed stream 31 is cooled to -45°F in exchanger 10 by heat exchange with cool reflux separator vapor at -25°F (stream 35), with cold separator vapor at -88°F (stream 32), and with external propane refrigerant. (The decision as to whether to use more than one heat exchanger for the indicated cooling services will depend on a number of factors including, but not limited to, feed gas flow rate, heat exchanger size, stream temperatures, etc.)

The cooled and partially condensed stream 31a is flash expanded in expansion valve 11 to 415 psia, slightly above the operating pressure of deethanizer column 14. During expansion a part of the condensed liquid is vaporized, cooling the expanded stream 31b to -88°F before it enters separator 12, whereupon the vapor (stream 32) is separated from the condensed liquid (stream 33). The liquid (stream 33) from separator 12 is directed by level control valve 13 to heat exchanger 17 and is heated to -37°F by heat exchange with the overhead distillation stream 34 from deethanizer 14, whereupon heated stream 33b enters deethanizer 14 at a mid-column feed point to be stripped of its methane and C_2 components.

The deethanizer tower 14, operating at 400 psia, is a conventional distillation column containing a plurality of vertically spaced trays, one or more packed beds, or some combination of trays and packing. The deethanizer tower may consist of two sections: an upper section wherein any vapor contained in the top feed

is separated from its corresponding liquid portion, and wherein the vapor rising from the lower distillation or deethanizing section is combined with the vapor portion (if any) of the top feed to form distillation stream 34 which exits the top of the tower; and a lower deethanizing section that contains the trays and/or packing to provide the necessary contact between the liquids falling downward and the vapors rising upward. The deethanizing section also includes side reboiler 15 and reboiler 16 which heat and vaporize a portion of the liquid in the lower regions of the column to provide the stripping vapors which flow up the column to strip the liquid product, stream 37, of methane and C₂ components. A typical specification for the bottom liquid product is to have an ethane to propane+butane ratio of 0.02:1 on a molar basis. The liquid product stream 37 exits the bottom of the deethanizer at 206°F and flows to subsequent processing and/or storage.

The deethanizer overhead vapor (stream 34) at -4°F flows through heat exchanger 17 and is cooled to -25°F in heat exchange relation with the expanded separator liquids (stream 33a), partially condensing stream 34a. The partially condensed stream 34a enters reflux separator 18 where its condensed liquid is separated from the uncondensed vapor (stream 35) and becomes the liquid reflux stream 36, which is returned to deethanizer 14 by reflux pump 19. The reflux stream (stream 36a) enters column 14 at a top column feed point and contacts the vapors rising upward through the deethanizing section.

The vapor (stream 32) leaving separator 12 at -88°F passes countercurrently to incoming feed gas (stream 31) in heat exchanger 10 and is partially warmed as it provides cooling and partial condensation of the feed gas. The partially warmed separator vapor is then combined with the reflux separator vapor (stream 35) to form the residue gas, which is further warmed to 85°F (stream 38) as it also passes countercurrently to the incoming feed gas in heat exchanger 10. The residue gas is then re-compressed in one stage by compressor 20 driven by a supplemental power source which compresses the residue gas (stream 38a) to sales line pressure. After cooling in discharge cooler 21, the residue gas product (stream 38b) flows to the sales gas pipeline at 100°F and 1115 psia.

A summary of stream flow rates and energy consumptions for the

process illustrated in FIG. 1 is set forth in the following table:

TABLE I

(FIG. 1)

Stream Flow Summary - (Lb. Moles/Hr)

5	<u>Stream</u>	<u>Methane</u>	<u>Ethane</u>	<u>Propane</u>	<u>Butanes+</u>	<u>Total</u>
	31	12608	2297	951	588	16469
	32	10195	601	52	5	10867
	33	2413	1696	899	583	5602
	35	2413	1693	6	0	4123
10	38	12608	2294	58	5	14990
	37	0	3	893	583	1479

Recoveries*

Propane	93.88%
Butanes+	99.15%

15 Horsepower

Residue Compression	9,917
Refrigeration Compression	6,480

Total	16,397

20 Utility Heat, MBTU/Hr

Deethanizer Reboilers	29,591
-----------------------	--------

* (Based on un-rounded flow rates)

The plant operator of the existing processing plant depicted in FIG. 1 subsequently needed to process additional volumes of natural gas, in excess of the feed gas rate for which the plant was originally designed, at somewhat different processing conditions. FIG. 2 represents how the processing plant of FIG. 1 could be modified to increase capacity by applying a prior art process in accordance with U.S. Pat. No. 4,854,955. For clarity, the existing plant equipment in the FIG. 1 process that

could be reused in the modified FIG. 2 process arrangement is shown with dashed lines and the new equipment required is shown with solid lines. Due to changes in the natural gas supply to the existing plant, the feed gas composition and conditions considered in the process presented in FIG. 2 are not the same as those in FIG. 1. As a result, the component recovery levels and utility consumptions for the FIG. 1 process and the FIG. 2 process are not directly comparable.

In the simulation of the FIG. 2 process, feed gas enters at 95°F and a pressure of 915 psia as stream 31 and is split into two portions, stream 41 and stream 42. About 72 percent of feed stream 31 (stream 41) is routed to the existing plant equipment and cooled in exchanger 10 by heat exchange with a portion of the cool residue gas at -52°F (stream 48) and with external propane refrigerant. The cooled stream 41a enters separator 12 at -35°F and 890 psia where the vapor (stream 32) is separated from the condensed liquid (stream 33). The condensed liquid is flash expanded to slightly above the operating pressure of deethanizer 14 in expansion valve 13. As the stream is expanded, a portion of the liquid vaporizes, cooling the total stream 33a to a temperature of approximately -66°F. The expanded stream is then directed in heat exchange relation with the other portion (stream 42) of the feed gas in heat exchanger 53 and heated to -29°F (stream 33b).

The vapor from separator 12 (stream 32) enters a work expansion machine 50 in which mechanical energy is extracted from this portion of the high pressure feed. The machine 50 expands the vapor substantially isentropically from a pressure of about 890 psia to a pressure of about 403 psia, with the work expansion cooling the expanded stream 32a to a temperature of approximately -97°F. The typical commercially available expanders are capable of recovering on the order of 80-85% of the work theoretically available in an ideal isentropic expansion. The work recovered is often used to drive a centrifugal compressor (such as item 51), that can be used to re-compress the residue gas (stream 38b), for example. The expanded and partially condensed stream 32a is supplied as feed to an absorbing section in a lower region of separator/absorber tower 52. The liquid portion of the expanded stream commingles with liquids falling downward from the absorbing section and the combined liquid stream 46 exits the bottom of separator/absorber 52. The vapor

portion of the expanded stream rises upward through the absorbing section and is contacted with cold liquid falling downward. Note that stream 32a could alternatively be supplied to deethanizer 14 as indicated by the dashed line, but this would increase the amount of vapor traffic in the top fractionation stages. The existing fractionation trays in deethanizer 14 could not handle this additional vapor load, hence in the current application stream 32a is supplied to separator/absorber 52. The optimum feed location for this and all other feed streams in a particular circumstance will often depend on a number of factors such as existing equipment limitations (as seen in this case), as well as feed gas composition and conditions, plant size, etc.

The separator/absorber tower 52 is a conventional distillation column containing a plurality of vertically spaced trays, one or more packed beds, or some combination of trays and packing. As is often the case in natural gas processing plants, the separator/absorber tower may consist of two sections. The upper section is a separator wherein any vapor contained in the top feed is separated from its corresponding liquid portion, and wherein the vapor rising from the lower distillation or absorbing section is combined with the vapor portion (if any) of the top feed to form the distillation stream 44 which exits the top of the tower. The lower, absorbing section contains the trays and/or packing and provides the necessary contact between the liquids falling downward and the vapors rising upward to condense and absorb the propane and heavier components. The combined liquid stream 46 leaves the bottom of separator/absorber 52 at -78°F . It is supplied (stream 46a) to deethanizer 14 by pump 59 at a top column feed position.

Returning to the second portion (stream 42) of the feed gas, the remaining 28 percent of the feed gas enters heat exchanger 53 where it is cooled to -39°F and partially condensed by heat exchange with the other portion of the cool residue gas at -52°F (stream 47) and with the flash expanded separator liquid at -66°F (stream 33a). The cooled stream 42a then enters heat exchanger 54 and is further cooled and substantially condensed by heat exchange with the cold residue gas at -104°F (stream 38). The substantially condensed stream 42b at -94°F is then flash expanded through an appropriate expansion device, such as expansion valve 55, to slightly above the operating pressure of the fractionation tower 14. During expansion

a portion of the stream is vaporized, resulting in cooling of the total stream. In the process illustrated in FIG. 2, the expanded stream 42c leaving expansion valve 55 reaches a temperature of -133°F and is supplied to heat exchanger 56. This stream is warmed and further vaporized in heat exchanger 56 as it provides cooling and partial condensation of the distillation stream 44 rising from the fractionation stages of separator/absorber 52. The warmed stream 42d at a temperature of -93°F is then supplied together with the heated expanded stream 33b to deethanizer column 14 at a mid-column feed position as stream 43. Note that stream 42d could alternatively be supplied to separator/absorber 52 at a mid-column or bottom feed position as indicated by the dashed line, but this would have increased the quantity of liquid fed to the top stages of deethanizer 14 by pump 59. Without costly modifications and extended plant downtime, the existing fractionation trays in deethanizer 14 could not handle this additional liquid load, hence in the current application stream 42d is supplied to tower 14 at a point below the top stages. Again, the optimum feed location for this feed stream in a particular circumstance will often depend on a number of factors such as existing equipment limitations (as seen in this case), as well as feed gas composition and conditions, plant size, etc.

Distillation stream 44 from separator/absorber 52 is cooled from a temperature of -90°F to approximately -104°F (stream 44a) by heat exchange with stream 42c. The partially condensed stream 44a is supplied to reflux separator 57 operating at about 396 psia. The condensed liquid (stream 45) is separated, and returned to separator/absorber 52 as reflux stream 45a at a top column feed position by means of reflux pump 58. The vapor stream 38 from reflux separator 57 is the cold volatile residuc gas stream. (It should be noted that the existing reflux separator and reflux pump, items 18 and 19, respectively, in FIG. 1 could not be reused in the FIG. 2 process as items 57 and 58, respectively, because the much lower operating temperature for these equipment items in the FIG. 2 process would not be compatible with the metallurgy of items 18 and 19.)

Deethanizer 14 operates at a pressure of approximately 410 psia. It should be noted that the majority of the plant feed gas is not supplied to this tower but is instead fed to separator/absorber 52, reducing the vapor traffic in tower 14 and

allowing the desired increase in plant processing capacity. The liquid product stream 37 exits the bottom of the deethanizer at 220°F and flows to subsequent processing and/or storage. The overhead vapor distillation stream 34 at -50°F from the upper region of deethanizer 14 is supplied to separator/absorber 52 at a lower feed point so that the vapor is contacted with cold liquid falling downward to condense and absorb the propane and heavier components.

The cold residue gas stream 38 from reflux separator 57 passes countercurrently to a portion (stream 42a) of the feed gas in heat exchanger 54 where it is warmed to -52°F (stream 38a) as it provides further cooling and substantial condensation of stream 42b. The cool residue gas stream 38a is then divided into two portions, streams 47 and 48. Streams 47 and 48 pass countercurrently to the feed gas in heat exchangers 53 and 10, respectively, and are warmed to 80°F and 89°F (streams 47a and 48a, respectively) as the streams provide cooling and partial condensation of the feed gas. The two warmed streams 47a and 48a then recombine as residue gas stream 38b at a temperature of 85°F. This recombined stream is then re-compressed in two stages. The first stage is compressor 51 driven by expansion machine 50. The second stage is compressor 20 driven by a supplemental power source. The compressed stream 38d is then cooled to 105°F by heat exchanger 21 before the residue gas product (stream 38e) flows to the sales gas pipeline at the new line pressure of 840 psia.

A summary of stream flow rates and energy consumptions for the process illustrated in FIG. 2 is set forth in the table below:

TABLE II

(FIG. 2)

Stream Flow Summary - (Lb. Moles/Hr)

	<u>Stream</u>	<u>Methane</u>	<u>Ethane</u>	<u>Propane</u>	<u>Butanes+</u>	<u>Total</u>
5	31	17898 1441	636 594	20913		
	41	12797 1030	455 425	14953		
	42	5101 411	181 169	5960		
	32	11880 756	216 80	13168		
	33	917 274	239 345	1785		
10	34	6769 1469	116 7	8480		
	44	18937 2315	7 0	21619		
	45	1039 895	6 0	1954		
	46	751 805	331 87	1983		
	38	17898 1420	1 0	19665		
15	37	0 21	635 594	1248		

Recoveries *

Propane 99.76%

Butanes+ 100.00%

Horsepower

20 Residue Compression 9,705

Refrigeration Compression 2,939

Total 12,644

Utility Heat, MBTU/Hr

25 Deethanizer Reboilers 23,276

* (Based on un-rounded flow rates)

Comparison of the feed gas flow rates and utility consumptions in Table II above for the FIG. 2 process with those in Table I for the FIG. 1 process shows that the FIG. 2 process achieves a 27 percent increase in gas processing

capacity while improving propane recovery and butanes + recovery. Comparison of Tables I and II further shows that the improvement in throughput and yields was not simply the result of increasing the horsepower (utility) requirements. To the contrary, the residue compression horsepower for the FIG. 2 process is 2 percent lower than the FIG. 1 process (allowing reuse of the existing residue compressors without modification) and the refrigeration compression for the FIG. 2 process is less than half of the FIG. 1 process (allowing an existing refrigeration compressor to be used elsewhere).

DESCRIPTION OF THE INVENTION

10

In one embodiment, the present invention provides a process for the separation of a gas stream containing methane, C₂ components, C₃ components and heavier hydrocarbon components into a volatile residue gas fraction and a relatively less volatile fraction containing said C₂ components, C₃ components and heavier hydrocarbon components or

15 said C₃ components and heavier hydrocarbon components, which process comprises

(a) dividing said gas stream into gaseous first and second streams;

(b) cooling said gaseous first stream under pressure to condense substantially all of it and thereafter allowing it to expand to a lower pressure whereby it is further cooled;

(c) cooling said gaseous second stream under pressure and thereafter allowing it to

20 expand to said lower pressure; and

(d) fractionating said cooled expanded first and second streams at said lower pressure whereby the components of said relatively less volatile fraction are recovered;

characterised in that

25 (1) said expanded cooled first stream is directed into heat exchange relation with a warmer distillation stream which rises from fractionation stages of a distillation column, thereby cooling said distillation stream sufficiently to at least partially condense it;

(2) at least a portion of said cooled expanded second stream is intimately contacted with at least a portion of said at least partially condensed distillation stream in a contacting device containing at least a fractional theoretical separation stage, and thereafter

30 the vapors and liquids from said contacting device are separated;

(3) said liquids thereby recovered are supplied to said distillation column as a



- 14A -

liquid feed thereto;

(4) said vapors thereby recovered are directed into heat exchange relation with said gaseous first stream thereby to heat said vapors and supply said cooling of step (b), whereupon said heated vapors are thereafter discharged as said volatile residue gas
5 fraction; and

(5) the quantities and temperatures of said feed streams to said contacting device and said distillation column are effective to maintain the overhead temperatures of said contracting device and said distillation column at temperatures whereby the major portions of the components in said relatively less volatile fraction are recovered.

10 The invention also provides a process for the separation of a gas stream containing methane, C₂ components, C₃ components and heavier hydrocarbon components into a volatile residue gas fraction and a relatively less volatile fraction containing said C₂ components, C₃ components and heavier hydrocarbon components or said C₃ components and heavier hydrocarbon components, which process comprises

15 (a) cooling said gas stream under pressure and then dividing it into gaseous first and second streams;

(b) cooling said gaseous first stream under pressure to condense substantially all of it and thereafter allowing it to expand to a lower pressure whereby it is further cooled;

(c) allowing said gaseous second stream to expand to said lower pressure; and

20 (d) fractionating said cooled expanded first stream and said expanded second stream at said lower pressure whereby the components of said relatively less volatile fraction are recovered;

characterised in that

25 (1) said expanded cooled first stream is directed into heat exchange relation with a warmer distillation stream which rises from fractionation stages of a distillation column, thereby cooling said distillation stream sufficiently to at least partially condense it;

(2) at least a portion of said expanded second stream is intimately contacted with at least a portion of said at least partially condensed distillation stream in a contacting device containing at least a fractional theoretical separation stage, and thereafter the vapors and

30 liquids from said contacting device are separated;

(3) said liquids thereby recovered are supplied to said distillation column as a



- 14B -

liquid feed thereto;

(4) said vapors thereby recovered are directed into heat exchange relation with said gaseous first stream thereby to heat said vapors and supply said cooling of step (b), whereupon said heated vapors are thereafter discharged as said volatile residue gas

5 fraction; and

(5) the quantities and temperatures of said feed streams to said contacting device and said distillation column are effective to maintain the overhead temperatures of said contacting device and said distillation column at temperatures whereby the major portions of the components in said relatively less volatile fraction are recovered.

10 In another embodiment the invention provides a process for the separation of a gas stream containing methane, C₂ components, C₃ components and heavier hydrocarbon components into a volatile residue gas fraction and a relatively less volatile fraction containing said C₂ components, C₃ components and heavier hydrocarbon components or said C₃ components and heavier hydrocarbon components, which process comprises

15 (a) dividing said gas stream into gaseous first and second streams;

(b) cooling said gaseous first stream under pressure to condense substantially all of it and thereafter allowing it to expand to a lower pressure whereby it is further cooled;

(c) cooling said gaseous second stream under pressure sufficient to partially condense it and separating to provide a vapor stream and a condensed stream;

20 (d) allowing said vapor stream to expand to said lower pressure;

(e) allowing said condensed stream to expand to said lower pressure; and

(f) fractionating said cooled expanded first stream, said expanded vapor stream, and said expanded condensed stream at said lower pressure whereby the components of said relatively less volatile fraction are recovered;

25 characterised in that

(1) said expanded cooled first stream is directed into heat exchange relation with a warmer distillation stream which rises from fractionation stages of a distillation column, thereby cooling said distillation stream sufficiently to at least partially condense it;

(2) at least a portion of said expanded vapor stream is intimately contacted with at least a portion of said at least partially condensed distillation stream in a contacting device containing at least a fractional theoretical separation stage, and thereafter the vapors and



- 14C -

liquids from said contacting device are separated;

(3) said liquids thereby recovered are supplied to said distillation column as a liquid feed thereto;

(4) said vapors thereby recovered are directed into heat exchange relation with said
5 gaseous first stream thereby to heat said vapors and supply said cooling of step (b),
whereupon said heated vapors are thereafter discharged as said volatile residue gas
fraction; and

(5) the quantities and temperatures of said feed streams to said contacting device
and said distillation column are effective to maintain the overhead temperatures of said
10 contacting device and said distillation column at temperatures whereby the major portions
of the components in said relatively less volatile fraction are recovered.

The invention further provides a process for the separation of a gas stream
containing methane, C₂ components, C₃ components and heavier hydrocarbon components
in to a volatile residue gas fraction and a relatively less volatile fraction containing said C₂
15 components, C₃ components and heavier hydrocarbon components or said C₃ components
and heavier hydrocarbon components, which process comprises

(a) cooling said gas stream under pressure and then dividing it into gaseous first
and second streams;

(b) cooling said gaseous first stream under pressure to condense substantially all of
20 it and thereafter allowing it to expand to a lower pressure whereby it is further cooled;

(c) cooling said gaseous second stream under pressure sufficient to partially
condense it and separating to provide a vapor stream and a condensed stream;

(d) allowing said vapor stream to expand to said lower pressure;

(e) allowing said condensed stream to expand to said lower pressure; and

25 (f) fractionating said cooled expanded first stream, said expanded vapor stream,
and said expanded condensed stream at said lower pressure whereby the components of
said relatively less volatile fraction are recovered;

characterised in that

(1) said expanded cooled first stream is directed into heat exchange relation
30 with a warmer distillation stream which rises from fractionation stages of a distillation
column, thereby cooling said distillation stream sufficiently to at least partially condense it;



- 14D -

(2) at least a portion of said expanded vapor stream is intimately contacted with at least a portion of said at least partially condensed distillation stream in a contacting device containing at least a fractional theoretical separation stage, and thereafter the vapors and liquids from said contacting device are separated;

5 (3) said liquids thereby recovered are supplied to said distillation column as a liquid feed thereto;

(4) said vapors thereby recovered are directed into heat exchange relation with said gaseous first stream thereby to heat said vapors and supply said cooling a step (b), whereupon said heated vapors are thereafter discharged as said volatile residue gas
10 fraction; and

(5) the quantities and temperatures of said feed streams to said contacting device and said distillation column are effective to maintain the overhead temperatures of said contacting device and said distillation column at temperatures whereby the major portions of the components in said relatively less volatile fraction are recovered.

15 In yet another embodiment the invention provides a process for the separation of a gas stream containing methane, C₂ components, C₃ components and heavier hydrocarbon components into a volatile residue gas fraction and a relatively less volatile fraction containing said C₂ components, C₃ components and heavier hydrocarbon components or said C₃ components and heavier hydrocarbon components, which process comprises

20 (a) cooling said gas stream under pressure sufficient to partially condense it and separating to provide a vapor stream and a condensed stream;

(b) dividing said vapor stream into gaseous first and second streams;

(c) cooling said gaseous first stream under pressure to condense substantially all of it and thereafter allowing it to expand to a lower pressure whereby it is further cooled;

25 (d) allowing said gaseous second stream to expand to said lower pressure;

(e) allowing said condensed stream to expand to said lower pressure; and

(f) fractionating said cooled expanded first stream, said expanded second stream, and said expanded condensed stream and said lower pressure whereby the components of said relatively less volatile fraction are recovered;

30 characterised in that

(1) said expanded cooled first stream is directed into heat exchange relation



- 14E -

with a warmer distillation stream which rises from fractionation stages of a distillation column, thereby cooling said distillation stream sufficiently to at least partially condense it;

(2) at least a portion of said expanded second stream is intimately contacted with at least a portion of said at least partially condensed distillation stream in a contacting
5 device containing at least a fractional theoretical separation stage, and thereafter the vapors and liquids from said contacting device are separated;

(3) said liquids thereby recovered are supplied to said distillation column as a liquid feed thereto;

(4) said vapors thereby recovered are directed into heat exchange relation
10 with said gaseous first stream thereby to heat said vapors and supply said cooling of step (c), whereupon said heated vapors are thereafter discharged as said volatile residue gas fraction; and

(5) the quantities and temperatures of said feed streams to said contacting device and said distillation column are effective to maintain the overhead temperatures of
15 said contacting device and said distillation column at temperatures whereby the major portions of the components in said relatively less volatile fraction are recovered.

In these processes, it is preferable that (a) vapor is separated from said at least partially condensed distillation stream before entering said contacting device, forming a residual vapor stream; and (b) said residual vapor stream is combined with said vapors
20 separated from said contacting device to form said volatile residue gas fraction, whereupon said volatile residue gas fraction is directed into heat exchange relation with said gaseous first stream thereby to heat said volatile residue gas fraction and supply said cooling of said gaseous first stream.

In yet another embodiment the invention provides a process for the separation of a
25 gas stream containing methane, C₂ components, C₃ components and heavier hydrocarbon components into a volatile residue gas fraction and a relatively less volatile fraction containing said C₂ components, C₃ components and heavier hydrocarbon components or said C₃ components and heavier hydrocarbon components, which process comprises

(a) cooling said gas stream under pressure sufficiently to partially condense it and separating to provide a vapor stream and a condensed stream;



- 14F -

- (b) dividing said vapor stream into gaseous first and second streams;
- (c) combining said gaseous first stream with at least a portion of said condensed stream to form a combined stream;
- (d) cooling said combined stream under pressure to condense substantially all of it
- 5 and allowing it to thereafter expand to a lower pressure whereby it is further cooled;
- (e) allowing said gaseous second stream to expand to said lower pressure; and
- (f) fractionating said cooled expanded combined stream, said expanded second stream, and any remaining portion of said condensed stream at said lower pressure whereby the components of said relatively less volatile fraction are recovered;
- 10 characterised in that
 - (1) said expanded cooled combined stream is directed into heat exchange relation with a warmer distillation stream which rises from fractionation stages of a distillation column, thereby cooling said distillation stream sufficiently to at least partially condense it;
 - 15 (2) at least a portion of said expanded second stream is intimately contacted with at least a portion of said at least partially condensed distillation stream in a contacting device containing at least a fractional theoretical separation stage, and thereafter the vapors and liquids from said contacting device are separated;
 - (3) said liquids thereby recovered are supplied to said distillation column as
 - 20 a liquid feed thereto;
 - (4) said vapors thereby recovered are directed into heat exchange relation with said combined stream thereby to heat said vapors and supply said cooling of step (d), whereupon said heated vapors are thereafter discharged as said volatile residue gas fraction; and
 - 25 (5) the quantities and temperatures of said feed streams to said contacting device and said distillation column are effective to maintain the overhead temperatures of said contacting device and said distillation column at temperatures whereby the major portions of the components in said relatively less volatile fraction are recovered. In this embodiment it is preferred that (a) vapor is separated from said at least partially condensed
 - 30 distillation stream before entering said contacting device, forming a residual vapor stream; and (b) said residual vapor stream is combined with said vapors separated from said



- 14G -

contacting device to form said volatile residue gas fraction, whereupon said volatile residue gas fraction is directed into heat exchange relation with said combined stream thereby to heat said volatile residue gas fraction and supply said cooling of said combined stream.

- 5 In a preferred embodiment of the present invention, in the process of the invention at least a portion of said liquids separated from said contacting device are heated before being supplied to said distillation column as a feed thereto.

The invention also relates to apparatus suitable for carrying out the processes of the present invention. Thus, in one embodiment the invention provides an apparatus for the
10 separation of a gas stream containing methane, C₂ components, C₃ components and heavier hydrocarbon components into a volatile residue gas fraction and a relatively less volatile fraction containing said C₂ components, C₃ components and heavier hydrocarbon components or said C₃ components and heavier hydrocarbon components said apparatus comprising

- 15 (a) a dividing means to divide said gas stream into gaseous first and second streams;

(b) a first heat exchange means connected to said dividing means to receive said gaseous first stream and to cool it under pressure sufficiently to substantially condense it;

- (c) a first expansion means connected to said first heat exchange means to receive
20 said substantially condensed first stream and to expand it to a lower pressure, whereby said stream is further cooled;

(d) a cooling means connected to said dividing means to receive said gaseous second stream and to cool it under pressure;

- (e) a second expansion means connected to said cooling means to receive said
25 cooled second stream and to expand it to said lower pressure; and

(f) a fractionation tower connected to said first expansion means and said second expansion means to receive said expanded streams therefrom;

characterised in that said apparatus further comprises

- (1) a second heat exchange means connected to said first expansion means to receive said expanded cooled first stream, said second heat exchange means being



- 14H -

further connected to said fractionation tower to receive a warmer distillation stream which rises from fractionation stages of a distillation column in said fractionation tower, thereby cooling said distillation stream sufficiently to at least partially condense it;

(2) a contacting and separating means connected to receive at least a portion
 5 of said at least partially condensed distillation stream and at least a portion of said cooled expanded second stream wherein said streams are commingled in at least one contacting device, said contacting and separating means including separating means to separate the vapor and liquid after contact in said contacting device to form a vapor stream and a liquid stream, said contacting and separating means being further connected to supply said liquid
 10 stream to said distillation column in said fractionation tower as a liquid feed thereto, said contacting and separating means being further connected to supply said vapor stream to said first heat exchange means to heat said vapor stream and thereby supply the cooling of step (b), whereupon said heated vapor stream is thereafter discharged as said volatile residue gas fraction; and

(3) control means adapted to regulate the quantities and temperatures of
 15 said feed streams to said contacting and separating means and said fractionation tower to maintain the overhead temperatures of said contacting and separating means and said fractionation tower at temperatures whereby the major portions of the components in said relatively less volatile fraction are recovered.

20 In another embodiment the invention provides an apparatus for the separation of a gas stream containing methane, C₂ components, C₃ components and heavier hydrocarbon components into a volatile residue gas fraction and a relatively less volatile fraction containing said C₂ components, C₃ components and heavier hydrocarbon components or said C₃ components and heavier hydrocarbon components, said apparatus comprising

- 25 (a) a cooling means to cool said gas stream under pressure;
 (b) a dividing means connected to said cooling means to receive said cooled gas stream and to divide it into gaseous first and second streams;
 (c) a first heat exchange means connected to said dividing means to receive said gaseous first stream and to cool it under pressure sufficiently to substantially condense it;
 (d) a first expansion means connected to said first heat exchange means to receive said substantially condensed first stream and to expand it to a lower pressure, whereby said



- 141 -

stream is further cooled;

(e) a second expansion means connected to said dividing means to receive said gaseous second stream and to expand it to said lower pressure; and

(f) a fractionation tower connected to said first expansion means and said second
5 expansion means to receive said expanded streams therefrom;

characterised in that said apparatus further comprises

(1) a second heat exchange means connected to said first expansion means to receive said expanded cooled first stream, said second heat exchange means being further connected to said fractionation tower to receive a warmer distillation stream which
10 rises from fractionation stages of a distillation column in said fractionation tower, thereby cooling said distillation stream sufficiently to at least partially condense it;

(2) a contacting and separating means connected to receive at least a portion of said at least partially condensed distillation stream and at least a portion of said expanded second stream wherein said streams are commingled in at least one contacting
15 device, said contacting and separating means including separating means to separate the vapor and liquid after contact in said contacting device to form a vapor stream and a liquid stream, said contacting and separating means being further connected to supply said liquid stream to said distillation column in said fractionation tower as a liquid feed thereto, said
20 contacting and separating means being further connected to supply said vapor stream to said first heat exchange means to heat said vapor stream and thereby supply the cooling of step (c), whereupon said heated vapor stream is thereafter discharged as said volatile residue gas fraction; and

(3) control means adapted to regulate the quantities and temperatures of said feed streams to said contacting and separating means and said fractionation tower to
25 maintain the overhead temperatures of said contacting and separating means and said fractionation tower at temperatures whereby the major portions of the components in said relatively less volatile fraction are recovered.

In these embodiments it is preferred that the apparatus comprises (a) a separation means connected to said second heat exchange means to receive said at least partially condensed distillation stream and separate it thereby to form a residual vapor stream and a liquid reflux stream, said separation means being further connected to supply said liquid



- 14J -

reflux stream to said contacting and separating means; and (b) a combining means connected to said separation means to receive said residual vapor stream, said combining means being further connected to said contacting and separating means to receive said vapor stream separated therefrom and combine it with said residual vapor stream to form
5 said volatile residue gas fraction, said combining means being further connected to supply said volatile residue gas fraction to said first heat exchange means, thereby heating said volatile residue gas fraction and supplying said cooling of said gaseous first stream.

In another embodiment the invention provides an apparatus for the separation of a gas stream containing methane, C₂ components, C₃ components and heavier hydrocarbon
10 components into a volatile residue gas fraction and a relatively less volatile fraction containing said C₂ components, C₃ components and heavier hydrocarbon components or said C₃ components and heavier hydrocarbon components, said apparatus comprising

3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30

(a) a dividing means to divide said gas stream into gaseous first and second streams;

15 (b) a first heat exchange means connected to said dividing means to receive said gaseous first stream and to cool it under pressure sufficiently to substantially condense it;

(c) a first expansion means connected to said first heat exchange means to receive said substantially condensed first stream and to expand it to a lower pressure, whereby said stream is further cooled;

20 (d) a cooling means connected to said dividing means to receive said gaseous second stream and to cool it under pressure sufficiently to partially condense it;

(e) a separation means connected to said cooling means to receive said cooled second stream and separate it thereby to provide a first vapor stream and a condensed stream;

25 (f) a second expansion means connected to said separation means to receive said first vapor stream and to expand it to said lower pressure;

(g) a third expansion means connected to said separation means to receive said condensed stream and to expand it to said lower pressure; and

(h) a fractionation tower connected to said first expansion means, said second expansion means, and said third expansion means to receive said expanded streams therefrom;



- 14K -

characterised in that said apparatus further comprises

(1) a second heat exchange means connected to said first expansion means to receive said expanded cooled first stream, said second heat exchange means being further connected to said fractionation tower to receive a warmer distillation stream which rises from fractionation stages of a distillation column in said fractionation tower, thereby cooling said distillation stream sufficiently to at least partially condense it;

(2) a contacting and separating means connected to receive at least a portion of said at least partially condensed distillation stream and at least a portion of said expanded first vapor stream wherein said streams are commingled in at least one contacting device, said contacting and separating means including separating means to separate the vapor and liquid after contact in said contacting device to form a second vapor stream and a liquid stream, said contacting and separating means being further connected to supply said liquid stream to said distillation column in said fractionation tower as a liquid feed thereto, said contacting and separating means being further connected to supply said second vapor stream to said first heat exchange means to heat said second vapor stream and thereby supply the cooling of step (b), whereupon said heated second vapor stream is thereafter discharged as said volatile residue gas fraction; and

(3) control means adapted to regulate the quantities and temperatures of said feed streams to said contacting and separating means and said fractionation tower to maintain the overhead temperatures of said contacting and separating means and said fractionation tower at temperatures whereby the major portions of the components in said relatively less volatile fraction are recovered.

In a further embodiment the invention provides an apparatus for the separation of a gas stream containing methane, C₂ components, C₃ components and heavier hydrocarbon components into a volatile residue gas fraction and a relatively less volatile fraction containing said C₂ components, C₃ components and heavier hydrocarbon components or said C₃ components and heavier hydrocarbon components, said apparatus comprising

(a) a first cooling means to cool said gas stream under pressure;

(b) a dividing means connected to first cooling means to receive said cooled gas stream and to divide it into gaseous first and second streams;

(c) a first heat exchange means connected to said dividing means to receive said



- 14L -

gaseous first stream and to cool it under pressure sufficiently to substantially condense it;

(d) a first expansion means connected to said first heat exchange means to receive said substantially condensed first stream and to expand it to a lower pressure, whereby said stream is further cooled;

5 (e) a second cooling means connected to said dividing means to receive said gaseous second stream and to cool it under pressure sufficiently to partially condense it;

(f) a separation means connected to said second cooling means to receive said cooled second stream and separate it thereby to provide a first vapor stream and a condensed stream;

10 (g) a second expansion means connected to said separation means to receive said first vapor stream and to expand it to said lower pressure;

(h) a third expansion means connected to said separation means to receive said condensed stream and to expand it to said lower pressure; and

(i) a fractionation tower connected to said first expansion means, said second
15 expansion means, and said third expansion means to receive said expanded streams therefrom;

characterised in that said apparatus further comprises

(1) a second heat exchange means connected to said first expansion means
to receive said expanded cooled first stream, said second heat exchange means being
20 further connected to said fractionation tower to receive a warmer distillation stream which rises from fractionation stages of a distillation column in said fractionation tower, thereby cooling said distillation stream sufficiently to at least partially condense it;

(2) a contacting and separating means connected to receive at least a portion
of said at least partially condensed distillation stream and at least a portion of said
25 expanded first vapor stream wherein said streams are commingled in at least one contacting device, said contacting and separating means including separating means to separate the vapor and liquid after contact in said contacting in said contacting device to form a second vapor and a liquid stream, said contacting and separating means being further connected to supply said liquid stream to said distillation column in said
30 fractionation tower as a liquid feed thereto, said contacting and separating means being further connected to supply said second vapor stream to said first heat exchange means to



- 14M -

heat said second vapor stream and thereby supply the cooling of step (c), whereupon said heated second vapor stream is thereafter discharged as said volatile residue gas fraction; and

(3) control means adapted to regulate the quantities and temperatures of said feed streams to said contacting and separating means and said fractionation tower to maintain the overhead temperatures of said contacting and separating means and said fractionation tower at temperatures whereby the major portions of the components in said relatively less volatile fraction are recovered.

In yet another embodiment the invention provides an apparatus for the separation of a gas stream containing methane, C₂ components, C₃ components and heavier hydrocarbon components into a volatile residue gas fraction and a relatively less volatile fraction containing said C₂ components, C₃ components and heavier hydrocarbon components or said C₃ components and heavier hydrocarbon components, said apparatus comprising

(a) a cooling means to cool said gas stream under pressure sufficiently to partially condense it;

(b) a separation means connected to said cooling means to receive said cooled gas stream and separate it thereby to provide a first vapor stream and a condensed stream;

(c) a dividing means connected to said separation means to receive said first vapor stream and to divide it into gaseous first and second streams;

(d) a first heat exchange means connected to said dividing means to receive said gaseous first stream and to cool it under pressure sufficiently to substantially condense it;

(e) a first expansion means connected to said first heat exchange means to receive said substantially condensed first stream and to expand it to a lower pressure, whereby said stream is further cooled;

(f) a second expansion means connected to said dividing means to receive said gaseous second stream and to expand it to said lower pressure;

(g) a third expansion means connected to said separation means to receive said condensed stream and to expand it to said lower pressure; and

(h) a fractionation tower connected to said first expansion means, said second expansion means, and said third expansion means to receive said expanded streams



- 14N -

therefrom;

characterised in that said apparatus further comprises

(1) a second heat exchange means connected to said first expansion means to receive said expanded cooled first stream, said second heat exchange means being
5 further connected to said fractionation tower to receive a warmer distillation stream which rises from fractionation stages of a distillation column in said fractionation tower, thereby cooling said distillation stream sufficiently to at least partially condense it;

(2) a contacting and separating means connected to receive at least a portion of said at least partially condensed distillation stream and at least a portion of said
10 expanded second stream wherein said streams are commingled in at least one contacting device, said contacting and separating means including separating means to separate the vapor and liquid after contact in said contacting device to form a second vapor stream and a liquid stream, said contacting and separating means being further connected to supply said liquid stream to said distillation column in said fractionation tower as a liquid feed
15 thereto, said contacting and separating means being further connected to supply said second vapor stream to said first heat exchange means to heat said second vapor stream and thereby supply the cooling of step (d), whereupon said heated second vapor stream is thereafter discharged as said volatile residue gas fraction; and

(3) control means adapted to regulate the quantities and temperatures of
20 said feed streams to said contacting and separating means and said fractionation tower to maintain the overhead temperatures of said contacting and separating means and said fractionation tower at temperatures whereby the major portions of the components in said relatively less volatile fraction are recovered.

In these last three embodiments it is preferred that the apparatus comprises (a) a
25 second separation means connected to said second heat exchange means to receive said at least partially condensed distillation stream and separate it thereby to form a residual vapor stream and a liquid reflux stream, said second separation means being further connected to supply said liquid reflux stream to said contacting and separating means; and (b) a combining means connected to said second separation means to receive said residual vapor stream, said combining means being further connected to said contacting and separating means to receive said second vapor stream separated therefrom and combine it with said



- 140 -

residual vapor stream to form said volatile residue gas fraction, said combining means being further connected to supply said volatile residue gas fraction to said first heat exchange means, thereby heating said volatile residue gas fraction and supplying said cooling of said gaseous first stream.

5 In yet a further embodiment the invention provides an apparatus according to any one of claims 10 to 15 which comprises a heating means connected to said contacting and separating means to receive at least a portion of said liquid stream separated therefrom and heat it, said heating means being further connected to supply said heated stream to said distillation column in said fractionation tower as a feed thereto.

10 In this embodiment the apparatus preferably comprises (a) a second separation means connected to said second heat exchange means to receive said at least partially condensed distillation stream and separate it thereby to form a residual vapor stream and a liquid reflux stream, said second separation means being further connected to supply said liquid reflux stream to said contacting and separating means; and (b) a combining means
15 connected to said second separation means to receive said residual vapor stream, said combining means being further connected to said contacting and separating means to receive said second vapor stream separated therefrom and combine it with said residual vapor stream to form said volatile residue gas fraction, said combining means being further connected to supply said volatile residue gas fraction to said first heat exchange means,
20 thereby heating said volatile residue gas fraction and supplying said cooling of said combined stream.

In the various embodiments of the invention it is preferred that the apparatus comprises a heating means connected to said contacting and separating means to receive at least a portion of said liquid stream separated therefrom and heat it, said heating means
25 being further connected to supply said heated stream to said distillation column in said fractionation tower as a feed thereto.

Example 1

FIG. 3 illustrates how the processing plant of FIG. can be modified in



- 14P -

accordance with the present invention. The feed gas composition and conditions considered in the process presented in FIG. 3 are the same as those in FIG. 2. Accordingly, the FIG. 3 process can be compared with that of the FIG. 2 process to illustrate the advantages of the present invention. In the simulation of this process, as in
 5 the simulation for the process of FIG. 2, operating conditions were selected to maximize recovery level for a given energy consumption. For clarity, the existing plant equipment in the FIG. 1 process that can be reused in the modified FIG. 3 process arrangement is shown with dashed lines and the new equipment required is shown with solid lines.

The feed gas splitting, cooling, partial condensation, and separation scheme is
 10 essentially the same as that used in FIG. 2. The difference lies in the manner in which the substantially condensed and flash expanded stream 42c is used to generate reflux for the separator/absorber 52. During flash expansion in expansion valve 55, a portion of the liquid in stream 42b vaporizes, cooling the total stream to -132°F (stream 42c). The expanded stream 42c is then supplied to heat exchanger 56 where it is warmed and further
 15 vaporized as it provides cooling and partial condensation of the distillation stream 34 rising from the upper region of deethanizer

3
 5
 7
 9
 11
 13
 15
 17
 19
 21
 23
 25
 27
 29
 31
 33
 35
 37
 39
 41
 43
 45
 47
 49
 51
 53
 55
 57
 59
 61
 63
 65
 67
 69
 71
 73
 75
 77
 79
 81
 83
 85
 87
 89
 91
 93
 95
 97
 99



14. The warmed stream 42d at a temperature of -60°F is then supplied together with the heated expanded stream 33b to deethanizer column 14 at a mid-column feed position as stream 43. (As noted previously for the FIG. 2 process, stream 42d could alternatively be supplied to separator/absorber 52 at a mid-column or bottom feed position as indicated by the dashed line, but this would have increased the quantity of liquid fed to the top stages of deethanizer 14 by pump 59. For this particular case, stream 42d is supplied to tower 14 at a point below the top stages to reduce the load on the fractionation trays in the upper section of the tower.)

Distillation stream 34 is cooled from a temperature of -56°F to approximately -98°F (stream 34a) by heat exchange with stream 42c. The partially condensed stream 34a is then supplied to the separator section in separator/absorber tower 52 where the condensed liquid is separated from the uncondensed vapor. The uncondensed vapor combines with the vapor rising from the lower absorbing section to form the cold distillation stream 38 leaving the upper region of separator/absorber 52 at a temperature of -102°F. The condensed liquid portion of stream 34a becomes the cold liquid (reflux) falling downward which contacts the vapor portion of the expanded stream 32a rising upward through the absorbing section of separator/absorber 52, condensing and absorbing the propane and heavier components contained in the vapor.

Deethanizer 14 operates at a pressure of approximately 404 psia. As noted earlier for the FIG. 2 process, the majority of the plant feed gas is not supplied to this tower but is instead fed to separator/absorber 52, reducing the vapor traffic in tower 14 and allowing the desired increase in plant processing capacity. The liquid product stream 37 exits the bottom of the deethanizer at 218°F and flows to subsequent processing and/or storage. The overhead vapor distillation stream 34 at -56°F from the upper region of deethanizer 14 is partially condensed and supplied to separator/absorber 52 at a top feed position as described earlier.

The distillation stream leaving the upper region of separator/absorber 52 is the cold residue gas stream 38 at -102°F, which passes countercurrently to a portion (stream 42a) of the feed gas in heat exchanger 54 where it is warmed to -53°F (stream 38a) as it provides further cooling and substantial condensation of stream

- 42b. The cool residue gas stream 38a is then divided into two portions, streams 47 and 48. Streams 47 and 48 pass countercurrently to the feed gas in heat exchangers 53 and 10, respectively, and are warmed to 80°F and 89°F (streams 47a and 48a, respectively) as the streams provide cooling and partial condensation of the feed gas.
- 5 The two warmed streams 47a and 48a then recombine as residue gas stream 38b at a temperature of 85°F. This recombined stream is then re-compressed in two stages. The first stage is compressor 51 driven by expansion machine 50. The second stage is compressor 20 driven by a supplemental power source. The compressed stream 38d is then cooled to 105°F by heat exchanger 21 before the residue gas product (stream
- 10 38e) flows to the sales gas pipeline at the new line pressure of 840 psia.

A summary of stream flow rates and energy consumptions for the process illustrated in FIG. 3 is set forth in the table below:

TABLE III

(FIG. 3)

Stream Flow Summary - (Lb. Moles/Hr)

	<u>Stream</u>	<u>Methane</u>	<u>Ethane</u>	<u>Propane</u>	<u>Butanes+</u>	<u>Total</u>
5	31	17898	1441	636	594	20913
	41	12886	1037	458	428	15058
	42	5012	404	178	166	5855
	32	11957	760	217	80	13252
	33	929	277	241	348	1806
10	34	7555	1750	70	5	9507
	46	1614	1089	273	85	3081
	38	17898	1421	14	0	19678
	37	0	20	622	594	1235

Recoveries *

15	Propane	97.83%
	Butanes+	99.96%

Horsepower

	Residue Compression	9,705
	Refrigeration Compression	2,947
20	Total	12,652

Utility Heat, MBTU/Hr

	Deethanizer Reboilers	23,352
--	-----------------------	--------

* (Based on un-rounded flow rates)

25 Comparison of the feed gas flow rates and utility consumptions in Table III above for the FIG. 3 process with those in Table I for the FIG. 1 process shows that the FIG. 3 process also achieves a 27 percent increase in gas processing capacity while improving propane recovery and butanes+ recovery. Comparison of Tables I and III further shows that the improvement in throughput and yields was not

simply the result of increasing the horsepower (utility) requirements. To the contrary, the residue compression horsepower for the FIG. 3 process is 2 percent lower than the FIG. 1 process (allowing reuse of the existing residue compressors without modification) and the refrigeration compression for the FIG. 3 process is less than half of the FIG. 1 process (allowing an existing refrigeration compressor to be used elsewhere).

Comparing the present invention to the prior art process displayed in FIG. 2, Tables II and III show that the present invention process very nearly matches the recovery efficiency of the FIG. 2 prior art process for C_3+ components. However, unlike the FIG. 2 process when it is adapted to an existing processing facility, the present invention does not require a reflux separator and reflux pump to provide the reflux stream for the separator/absorber, substantially reducing the capital cost for modifying the FIG. 1 process to achieve higher processing capacity and higher C_3+ product recovery levels.

The FIG. 3 process creates an absorption cooling effect inside separator/absorber 52 similar to that described in U.S. Pat. No. 4,617,039, wherein the saturation of the vapors rising upward through the tower by vaporization of liquid methane and ethane contained in the condensed liquid portion of stream 34a provides refrigeration to the tower. Note that, as a result, both the vapor leaving the overhead of the tower and the liquids leaving the bottom of the tower are colder than the respective feed streams at those ends of the tower. This absorption cooling effect allows the tower bottoms (stream 46) to be colder, creating a more effective reflux stream (stream 46a) for the deethanizer. Comparing the deethanizer overhead stream (stream 34 in FIGS. 2 and 3) in Tables II and III shows that the C_3+ concentration of the tower overhead in the FIG. 3 process is only half as much as that in the FIG. 2 process as a result of this absorption cooling effect.

Example 2

FIG. 4 illustrates how the processing plant of FIG. 1 can be modified in accordance with an alternative embodiment of the present invention. The feed gas composition and conditions considered in the process presented in FIG. 4 are the same

as those in FIG. 3. For clarity, the existing plant equipment in the FIG. 1 process that can be reused in the modified FIG. 4 process arrangement is shown with dashed lines and the new equipment required is shown with solid lines.

The feed gas splitting, cooling, partial condensation, and separation scheme is similar to that used in FIG. 3. The main difference is that a portion of the liquid stream from the bottom of separator/absorber 52 is used for feed gas cooling, allowing greater cooling of the feed gas while reducing the heat exchange required from gas stream 48. In the simulation of the FIG. 4 process, feed gas enters at 95°F and a pressure of 915 psia as stream 31 and is split into two portions, stream 41 and stream 42. About 72 percent of feed stream 31 (stream 41) is routed to the existing plant equipment and cooled in exchanger 10 by heat exchange with a portion of the cool residue gas at -54°F (stream 48), with external propane refrigerant, and with a portion of the liquid stream from the bottom of separator/absorber 52 at -107°F (stream 61). The cooled stream 41a enters separator 12 at -36°F and 890 psia where the vapor (stream 32) is separated from the condensed liquid (stream 33) and is then work expanded and supplied to separator/absorber 52 as described previously. The condensed liquid is flash expanded and used for heat exchange as described previously.

Liquid stream 46 leaves the bottom of separator/absorber 52 at -107°F and enters pump 59. Stream 46a from pump 59 is then split into two portions, stream 60 and stream 61. About 80% of stream 46a (stream 60) is directed to deethanizer 14 at a top column feed position as described previously. The remaining portion (stream 61) is directed to heat exchanger 10 where it provides cooling to the feed gas as described previously as it is heated to -36°F and partially vaporized. The warmed stream 61a at a temperature of -36°F is then supplied together with the warmed stream 42d and the heated expanded stream 33b to deethanizer column 14 at a mid-column feed position as stream 43. (For the FIGS. 3 and 4 processes, all or a part of stream 42d could alternatively be supplied to separator/absorber 52 at a mid-column or bottom feed position as indicated by the dashed line, but this increases the quantity of liquid fed to the top stages of deethanizer 14 by pump 59. For this particular case, stream 42d is supplied to tower 14 at a point below the top stages to reduce the load

on the fractionation trays in the upper section of the tower. Also, all or a part of stream 61a could alternatively be supplied separately to deethanizer 14 at a lower mid-column feed position as shown by the dashed line, but this requires adding another feed tray to existing deethanizer 14. For this particular case, combining
5 stream 61a with the other two streams was deemed to be the more economical alternative.)

The other features of the process of FIG. 4 are substantially the same as the process of FIG. 3 described previously. A summary of stream flow rates and energy consumptions for the process illustrated in FIG. 4 is set forth in the table
10 below:

TABLE IV

(FIG. 4)

Stream Flow Summary - (Lb. Moles/Hr)

<u>Stream</u>	<u>Methane</u>	<u>Ethane</u>	<u>Propane</u>	<u>Butanes+</u>	<u>Total</u>
5 31	17898	1441	636	594	20913
41	12886	1037	458	428	15058
42	5012	404	178	166	5855
32	11928	753	213	78	13210
33	958	284	245	350	1848
10 34	7633	1791	68	4	9624
46	1663	1123	268	82	3157
38	17898	1421	13	0	19677
37	0	20	623	594	1236

Recoveries *

15	Propane	97.99%
	Butanes+	99.97%

Horsepower

	Residue Compression	9,709
	Refrigeration Compression	2,944
20		-----
	Total	12,653

Utility Heat, MBTU/Hr

	Deethanizer Reboilers	21,919
--	-----------------------	--------

* (Based on un-rounded flow rates)

25 As before for the FIG. 3 process, the alternative embodiment of the present invention as applied in FIG. 4 can achieve a 27 percent increase in gas processing capacity. Comparison of the utility consumptions of the FIG. 3 embodiment of the present invention displayed in Table III with the utility consumptions of the FIG. 4 embodiment of the present invention displayed in

Table IV shows that the better heat integration possible with the FIG. 4 embodiment reduces the utility heat requirement by more than 5 percent while improving the propane recovery from 97.83% to 97.99%. The choice of whether to use the slightly more complicated FIG. 4 embodiment of the present invention will usually be based on economics, and will be influenced by such factors as plant size and available equipment, relative values of products and utility heat, and the composition of the feed gas.

Example 3

FIG. 3 represents the preferred embodiment of the present invention for the temperature and pressure conditions shown when modifying an existing processing plant for recovery of C_3+ components in the liquid product while rejecting C_2 components and more volatile components to the residue gas is desired. FIG. 5 represents an alternative embodiment of the present invention when modification of an existing processing plant for recovery of a significant amount of the C_2 components in the liquid product is desired. The feed gas composition and conditions considered in the process presented in FIG. 5 are the same as those in FIG. 3. For clarity, the existing plant equipment in the FIG. 1 process that can be reused in the modified FIG. 5 process arrangement is shown with dashed lines and the new equipment required is shown with solid lines.

In the simulation of the FIG. 5 process, feed gas enters at 95°F and a pressure of 915 psia as stream 31 and is split into two portions, stream 41 and stream 42. About 70 percent of feed stream 31 (stream 41) is routed to the existing plant equipment and cooled in exchanger 10 by heat exchange with a portion of the cool residue gas at -57°F (stream 48) and with external propane refrigerant. The cooled stream 41a enters separator 12 at -32°F and 890 psia where the vapor (stream 32) is separated from the condensed liquid (stream 33). The condensed liquid is flash expanded to slightly above the operating pressure of demethanizer 14 in expansion valve 13. As the stream is expanded, a portion of the liquid vaporizes, cooling the total stream 33a to a temperature of approximately -65°F. The expanded stream is

then directed in heat exchange relation with the other portion (stream 42) of the feed gas in heat exchanger 53 and heated to -28°F (stream 33b), and thereafter supplied to demethanizer 14 at a mid-column feed position.

The vapor from separator 12 (stream 32) enters a work expansion machine 50 in which mechanical energy is extracted from this portion of the high pressure feed. The machine 50 expands the vapor substantially isentropically from a pressure of about 890 psia to a pressure of about 378 psia, with the work expansion cooling the expanded stream 32a to a temperature of approximately -99°F . The expanded and partially condensed stream 32a is supplied as feed to an absorbing section in a lower region of separator/absorber tower 52. The liquid portion of the expanded stream commingles with liquids falling downward from the absorbing section and the combined liquid stream 46 exits the bottom of separator/absorber 52 at -106°F and is supplied (stream 46a) to demethanizer 14 by pump 59 at a top column feed position. The vapor portion of the expanded stream rises upward through the absorbing section and is contacted with cold liquid falling downward.

Returning to the second portion (stream 42) of the feed gas, the remaining 30 percent of the feed gas enters heat exchanger 53 where it is cooled and partially condensed by heat exchange with the other portion of the cool residue gas at -57°F (stream 47) and with the flash expanded separator liquid at -65°F (stream 33a). The cooled stream 42a at -38°F then enters heat exchanger 54 and is further cooled and substantially condensed by heat exchange with the cold residue gas (stream 38) at -141°F . The substantially condensed stream 42b at -134°F is then flash expanded through an appropriate expansion device, such as expansion valve 55, to slightly above the operating pressure of the separator/absorber 52. During expansion a portion of the stream is vaporized, resulting in cooling of the total stream. In the process illustrated in FIG. 5, the expanded stream 42c leaving expansion valve 55 reaches a temperature of -141°F and is supplied to heat exchanger 56 where it is warmed and partially vaporized as it provides cooling and partial condensation of the distillation stream 34 rising from the upper region of demethanizer 14. The warmed stream 42d at a temperature of -138°F is then supplied to separator/absorber 52 at a mid-column feed position.

It should be noted that when the process of FIG. 5 is operated to recover C_2 components in the bottom product of tower 14 (rather than to reject C_2 components to the residue gas as in the FIG. 3 process), less reboiler heat is required to meet the bottom product specification for tower 14. The resulting decrease in vapor and liquid traffic in the fractionation stages reduces the load on the top stages of tower 14, so that in this example it is possible to supply the warmed expanded stream 42d to separator/absorber 52 at the optimum mid-column feed position without overloading the top fractionation stages in tower 14 with the liquids (stream 46a) supplied to tower 14 from the bottom of separator/absorber 52.

Distillation stream 34 is cooled to a temperature of approximately -139°F (stream 34a) by heat exchange with stream 42c. The partially condensed stream 34a is then supplied to the separator section in separator/absorber tower 52 where the condensed liquid is separated from the uncondensed vapor. The uncondensed vapor combines with the vapor rising from the lower absorbing section to form the cold distillation stream 38 leaving the upper region of separator/absorber 52 at -141°F . The condensed liquid portion of stream 34a becomes the cold liquid falling downward which contacts the vapor portions of the warmed expanded stream 42d and the expanded stream 32a rising upward through the absorbing section of separator/absorber 52, condensing and absorbing the ethane and heavier components contained in the vapor.

Demethanizer 14 operates at a pressure of approximately 385 psia. The liquid product stream 37 exits the bottom of the demethanizer at 93°F (based on a typical specification of a methane to ethane ratio of 0.02:1 on a molar basis in the bottom product) and flows to subsequent processing and/or storage. The overhead vapor distillation stream 34 at -104°F from the upper region of demethanizer 14 is partially condensed and supplied to separator/absorber 52 at a top feed position as described earlier.

The distillation stream leaving the upper region of separator/absorber 52 is the cold residue gas stream 38, which passes countercurrently to a portion (stream 42a) of the feed gas in heat exchanger 54 where it is warmed to -57°F (stream 38a) as it provides further cooling and substantial condensation of stream 42b. The

cool residue gas stream 38a is then divided into two portions, streams 47 and 48. Streams 47 and 48 pass countercurrently to the feed gas in heat exchangers 53 and 10, respectively, and are warmed to 80°F and 93°F (streams 47a and 48a, respectively) as the streams provide cooling and partial condensation of the feed gas. The two
5 warmed streams 47a and 48a then recombine as residue gas stream 38b at a temperature of 86°F. This recombined stream is then re-compressed in two stages. The first stage is compressor 51 driven by expansion machine 50. The second stage is compressor 20 driven by a supplemental power source. The compressed stream 38d is then cooled to 105°F by heat exchanger 21 before the residue gas product (stream
10 38e) flows to the sales gas pipeline at the new line pressure of 840 psia.

A summary of stream flow rates and energy consumptions for the process illustrated in FIG. 5 is set forth in the table below:

TABLE V

(FIG. 5)

Stream Flow Summary - (Lb. Moles/Hr)

<u>Stream</u>	<u>Methane</u>	<u>Ethane</u>	<u>Propane</u>	<u>Butanes+</u>	<u>Total</u>
5 31	17898	1441	636	594	20913
41	12529	1009	445	416	14640
42	5369	432	191	178	6273
32	11698	756	220	83	12989
33	831	253	225	333	1651
10 34	2572	124	7	1	2723
46	1765	1113	415	262	3585
38	17874	199	3	0	18400
37	24	1242	633	594	2513

Recoveries

15	Ethane	86.20%
	Propane	99.52%
	Butanes+	99.99%

Horsepower

	Residue Compression	9,776
20	Refrigeration Compression	2,947
	Total	12,723

Utility Heat, MBTU/Hr

	Demethanizer Reboilers	14,492
--	------------------------	--------

25 * (Based on un-rounded flow rates)

As before for the FIG. 3 process, the present invention as applied in FIG. 5 can achieve a 27 percent increase in gas processing capacity. In addition, however, with only a minor adjustment in processing conditions and feed stream arrangement, the FIG. 5 process can recover 86.20% of the ethane contained in the

feed gas, plus 99.52% of the propane and 99.99% of the butanes+, with no increase in operating utilities. The only significant differences between the present invention as depicted in FIG. 3 and as depicted in FIG. 5 is the feed location of the warmed expanded stream 42d and the amount of heat supplied to tower 14 by side reboiler 15 and reboiler 16. These two simple changes allow the present invention to switch from high propane recovery with near complete ethane rejection (FIG. 3) to high ethane recovery (FIG. 5). This allows the plant operator to easily adjust plant operations to produce maximum product revenues as the prices of natural gas and ethane product fluctuate.

10

Other Embodiments

In accordance with this invention, it is generally advantageous to design the separator/absorber to provide a contacting device composed of multiple theoretical separation stages. However, the benefits of the present invention can be achieved with as few as one theoretical stage, and it is believed that even the equivalent of a fractional theoretical stage may allow achieving these benefits. For instance, all or a part of the partially condensed stream leaving heat exchanger 56 and all or a part of the partially condensed stream from work expansion machine 50 in FIGS. 3, 4, and 5 can be combined (such as in the piping joining the expansion machine to the separator/absorber) and if thoroughly intermingled, the vapors and liquids will mix together and separate in accordance with the relative volatilities of the various components of the total combined streams. In such an embodiment, the vapor-liquid mixture from heat exchanger 56 can be used without separation, or the liquid portion thereof may be separated. Such commingling of the two streams shall be considered for the purposes of this invention as constituting a contacting device. In another variation of the foregoing, the partially condensed stream from heat exchanger 56 can be separated, and then all or a part of the separated liquid supplied to the separator/absorber or mixed with the vapors fed thereto.

As described earlier in the preferred embodiments, the overhead vapors from the deethanizer (or demethanizer) are partially condensed and used to absorb valuable C₂ components, C₃ components, and heavier components from the vapors

leaving the work expansion machine. However, the present invention is not limited to this embodiment. It may be advantageous, for instance, to treat only a portion of the outlet vapor from the work expansion machine in this manner, or to use only a portion of the overhead condensate as an absorbent, in cases where other design

- 5 considerations indicate portions of the expansion machine outlet or overhead condensate should bypass the separator/absorber. Feed gas conditions, plant size, available equipment, or other factors may indicate that elimination of work expansion machine 50, or replacement with an alternative expansion device (such as an expansion valve), is feasible, or that total (rather than partial) condensation of the
- 10 overhead stream in heat exchanger 56 is possible or is preferred.

- It should also be noted that the separator/absorber can be constructed either as a separate vessel or as a section of the deethanizer (or demethanizer) column. For example, FIG. 6 illustrates how the present invention might be applied in the case of a new plant installation (rather than modification of an existing processing plant as
- 15 heretofore described) with a single fractionation column containing both a separator/absorber section and a deethanizing (or demethanizing) section. In this embodiment of the present invention, distillation stream 34 is withdrawn from the upper region of the deethanizing (or demethanizing) section contained in fractionation tower 14 and directed to heat exchanger 56. The distillation stream is cooled and
- 20 partially condensed by heat exchange with the substantially condensed and flash expanded stream 42b, and the partially condensed stream 34a then enters reflux separator 57 where the condensed liquid (stream 45) is separated from the uncondensed vapor (stream 44). The condensed liquid is supplied to fractionation tower 14 at a top feed position by reflux pump 58 as stream 45a to provide reflux for
- 25 the separator/absorber section in the top of the tower. The uncondensed vapor (stream 44) joins the tower overhead (stream 43) to form the cold residue gas, stream 38. The warmed expanded stream 42c leaving heat exchanger 56 is supplied to fractionation tower 14 at a mid-column feed point. Depending on whether the plant is operated to recover the C_2+ components or the C_3+ components in the bottom product, the feed
- 30 gas composition and conditions, and other factors, the optimum feed location for stream 42c may be above the work expanded stream 41a, below the work expanded

stream 41a but above the withdrawal point of distillation stream 34, or below the withdrawal point of distillation stream 34, or any combination thereof. Similarly, the optimum feed location for expanded stream 41a may be above the withdrawal point of distillation stream 34, or below the withdrawal point of distillation stream 34, or any combination thereof. The choice between the dual column arrangement depicted in FIGS. 3, 4, and 5 and the single column arrangement (requiring a reflux separator and reflux pump) will depend on a number of factors including, but not limited to, feed gas composition and conditions, plant size, equipment availability, etc.

In the practice of the present invention as depicted in FIGS. 3, 4, and 5, there will necessarily be a slight pressure difference between the deethanizer (or demethanizer) and the separator/absorber which must be taken into account. If the overhead vapors pass through heat exchanger 56 and into separator/absorber 52 without any boost in pressure, the separator/absorber shall necessarily assume an operating pressure slightly below the operating pressure of deethanizer (or demethanizer) 14. In this case, the combined liquid stream withdrawn from the separator/absorber can be pumped to its feed position in the deethanizer (or demethanizer). An alternative is to provide a booster blower in the vapor line to raise the operating pressure in heat exchanger 56 and separator/absorber 52 sufficiently so that the combined liquid stream can be supplied to deethanizer (or demethanizer) 14 without pumping. Still another alternative is to mount separator/absorber 52 at a sufficient elevation relative to the feed position on deethanizer (or demethanizer) 14 so that the hydrostatic head of the liquid will overcome the pressure difference.

The use and distribution of the separator liquids and the separator/absorber liquids for process heat exchange, the particular arrangement of heat exchangers for feed gas cooling, the choice of process streams for specific heat exchange services, and the use of external refrigeration to supplement the cooling available to the feed gas from other process streams must be evaluated for each particular application.

The high pressure liquid stream 33 in FIGS. 3 through 6 need not be expanded through an expansion valve, heated, and fed to a mid-column feed point on the distillation column. Some or all of this stream may be combined with the portion

of the feed gas (stream 42a in FIGS. 3, 4, and 5) or the separator vapor (stream 42 in FIG. 6) flowing to heat exchanger 54.

In accordance with this invention, the splitting of the vapor feed may be accomplished in several ways. In the processes of FIGS. 3, 4, and 5, the high pressure feed gas is split prior to any cooling of the feed gas. In the process of FIG. 6, the splitting of vapor occurs following cooling and separation of any liquids which may have been formed. Alternatively, the feed gas could be split after cooling of the gas and prior to any separation stages. In some embodiments, vapor splitting may be effected in a separator. Alternatively, the separator 12 in the processes shown in FIGS. 3 through 6 may be unnecessary if the feed gas is relatively lean. Moreover, the use of external refrigeration to supplement the cooling available to the feed gas from other process streams may be unnecessary, particularly in the case of a feed gas leaner than that used in Example 1. The use and distribution of deethanizer (or demethanizer) liquids for process heat exchange, and the particular arrangement of heat exchangers for feed gas cooling must be evaluated for each particular application, as well as the choice of process streams for specific heat exchange services.

It will also be recognized that the relative amount of feed found in each branch of the split vapor feed will depend on several factors, including gas pressure, feed gas composition, the amount of heat which can economically be extracted from the feed and the quantity of horsepower available. More feed to the column in the branch that is substantially condensed, expanded, and used to partially condense the distillation stream may increase recovery while decreasing power recovered from the work expansion machine thereby increasing the recompression horsepower requirements. Increasing feed to the work expansion machine reduces the horsepower consumption but may also reduce product recovery. The mid-column feed positions depicted in FIGS. 3 through 6 are the preferred feed locations for the process operating conditions described. However, the relative locations of the mid-column feeds may vary depending on feed gas composition or other factors such as desired recovery levels and amount of liquid formed during feed gas cooling. Moreover, two or more of the feed streams, or portions thereof, may be combined depending on the relative temperatures and quantities of individual streams, and the combined stream

- 31 -

then fed to a mid-column feed position. FIGS. 3 and 5 are the preferred embodiments for the compositions and operating conditions shown. Although individual stream expansion is depicted in particular expansion devices, alternative expansion means may be employed where appropriate. For example, conditions may warrant work expansion of the
5 substantially condensed portion of the feed stream (stream 42b in FIGS. 3, 4 and 5) or the substantially condensed portion of the separator vapor (stream 42a in Fig. 6).

While there have been described what are believed to be preferred embodiments of the invention, those skilled in the art will recognize that other and further modifications may be made thereto, e.g. to adapt the invention to various conditions, types of feed or
10 other requirements without departing from the spirit of the present invention as defined by the following claims.

Throughout this specification and the claims which follow, unless the context requires otherwise, the word "comprise", and variations such as "comprises" and "comprising", will be understood to imply the inclusion of a stated integer or step or group
15 of integers or steps but not the exclusion of any other integer or step or group of integers or steps.

The reference to any prior art in this specification is not, and should not be taken as, an acknowledgment or any form of suggestion that that prior art forms part of the common general knowledge in Australia..

3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847

THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. A process for the separation of a gas stream containing methane, C₂ components, C₃ components and heavier hydrocarbon components into a volatile residue gas fraction and a relatively less volatile fraction containing said C₂ components, C₃ components and heavier hydrocarbon components or said C₃ components and heavier hydrocarbon components, which process comprises

- (a) dividing said gas stream into gaseous first and second streams;
- (b) cooling said gaseous first stream under pressure to condense substantially all of it and thereafter allowing it to expand to a lower pressure whereby it is further cooled;
- (c) cooling said gaseous second stream under pressure and thereafter allowing it to expand to said lower pressure; and
- (d) fractionating said cooled expanded first and second streams at said lower pressure whereby the components of said relatively less volatile fraction are recovered;

characterised in that

- (1) said expanded cooled first stream is directed into heat exchange relation with a warmer distillation stream which rises from fractionation stages of a distillation column, thereby cooling said distillation stream sufficiently to at least partially condense it;
- (2) at least a portion of said cooled expanded second stream is intimately contacted with at least a portion of said at least partially condensed distillation stream in a contacting device containing at least a fractional theoretical separation stage, and thereafter the vapors and liquids from said contacting device are separated;
- (3) said liquids thereby recovered are supplied to said distillation column as a liquid feed thereto;
- (4) said vapors thereby recovered are directed into heat exchange relation with said gaseous first stream thereby to heat said vapors and supply said cooling of step (b), whereupon said heated vapors are thereafter discharged as said volatile residue gas fraction; and

(5) the quantities and temperatures of said feed streams to said contacting device and said distillation column are effective to maintain the overhead temperatures of said contracting device and said distillation column at temperatures whereby the major



- 33 -

portions of the components in said relatively less volatile fraction are recovered.

2. A process for the separation of a gas stream containing methane, C_2 components, C_3 components and heavier hydrocarbon components into a volatile residue gas fraction and a relatively less volatile fraction containing said C_2 components, C_3 components and heavier hydrocarbon components or said C_3 components and heavier hydrocarbon components, which process comprises

- (e) cooling said gas stream under pressure and then dividing it into gaseous first and second streams;
- 10 (f) cooling said gaseous first stream under pressure to condense substantially all of it and thereafter allowing it to expand to a lower pressure whereby it is further cooled;
- (g) allowing said gaseous second stream to expand to said lower pressure; and
- (h) fractionating said cooled expanded first stream and said expanded second stream at said lower pressure whereby the components of said relatively less volatile
- 15 fraction are recovered;
- characterised in that
- (6) said expanded cooled first stream is directed into heat exchange relation with a warmer distillation stream which rises from fractionation stages of a distillation column, thereby cooling said distillation stream sufficiently to at least partially condense it;
- 20 (7) at least a portion of said expanded second stream is intimately contacted with at least a portion of said at least partially condensed distillation stream in a contacting device containing at least a fractional theoretical separation stage, and thereafter the vapors and liquids from said contacting device are separated;
- (8) said liquids thereby recovered are supplied to said distillation column as a
- 25 liquid feed thereto;
- (9) said vapors thereby recovered are directed into heat exchange relation with said gaseous first stream thereby to heat said vapors and supply said cooling of step (b), whereupon said heated vapors are thereafter discharged as said volatile residue gas fraction; and
- 30 (10) the quantities and temperatures of said feed streams to said contacting device and said distillation column are effective to maintain the overhead temperatures of



said contacting device and said distillation column at temperatures whereby the major portions of the components in said relatively less volatile fraction are recovered.

3. A process for the separation of a gas stream containing methane, C₂ components,
5 C₃ components and heavier hydrocarbon components into a volatile residue gas fraction and a relatively less volatile fraction containing said C₂ components, C₃ components and heavier hydrocarbon components or said C₃ components and heavier hydrocarbon components, which process comprises
 - (g) dividing said gas stream into gaseous first and second streams;
 - 10 (h) cooling said gaseous first stream under pressure to condense substantially all of it and thereafter allowing it to expand to a lower pressure whereby it is further cooled;
 - (i) cooling said gaseous second stream under pressure sufficient to partially condense it and separating to provide a vapor stream and a condensed stream;
 - (j) allowing said vapor stream to expand to said lower pressure;
 - 15 (k) allowing said condensed stream to expand to said lower pressure; and
 - (l) fractionating said cooled expanded first stream, said expanded vapor stream, and said expanded condensed stream at said lower pressure whereby the components of said relatively less volatile fraction are recovered;characterised in that
 - 20 (6) said expanded cooled first stream is directed into heat exchange relation with a warmer distillation stream which rises from fractionation stages of a distillation column, thereby cooling said distillation stream sufficiently to at least partially condense it;
 - (7) at least a portion of said expanded vapor stream is intimately contacted with at least a portion of said at least partially condensed distillation stream in a contacting device
 - 25 containing at least a fractional theoretical separation stage, and thereafter the vapors and liquids from said contacting device are separated;
 - (8) said liquids thereby recovered are supplied to said distillation column as a liquid feed thereto;
 - (9) said vapors thereby recovered are directed into heat exchange relation with said
 - 30 gaseous first stream thereby to heat said vapors and supply said cooling of step (b), whereupon said heated vapors are thereafter discharged as said volatile residue gas



- 35 -

fraction; and

- (10) the quantities and temperatures of said feed streams to said contacting device and said distillation column are effective to maintain the overhead temperatures of said contacting device and said distillation column at temperatures whereby the major portions of the components in said relatively less volatile fraction are recovered.

4. A process for the separation of a gas stream containing methane, C_2 components, C_3 components and heavier hydrocarbon components in to a volatile residue gas fraction and a relatively less volatile fraction containing said C_2 components, C_3 components and heavier hydrocarbon components or said C_3 components and heavier hydrocarbon components, which process comprises

(g) cooling said gas stream under pressure and then dividing it into gaseous first and second streams;

(h) cooling said gaseous first stream under pressure to condense substantially all of it and thereafter allowing it to expand to a lower pressure whereby it is further cooled;

(i) cooling said gaseous second stream under pressure sufficient to partially condense it and separating to provide a vapor stream and a condensed stream;

(j) allowing said vapor stream to expand to said lower pressure;

(k) allowing said condensed stream to expand to said lower pressure; and

(l) fractionating said cooled expanded first stream, said expanded vapor stream, and said expanded condensed stream at said lower pressure whereby the components of said relatively less volatile fraction are recovered;

characterised in that

(6) said expanded cooled first stream is directed into heat exchange relation with a warmer distillation stream which rises from fractionation stages of a distillation column, thereby cooling said distillation stream sufficiently to at least partially condense it;

(7) at least a portion of said expanded vapor stream is intimately contacted with at least a portion of said at least partially condensed distillation stream in a contacting device containing at least a fractional theoretical separation stage, and thereafter the vapors and liquids from said contacting device are separated;

(8) said liquids thereby recovered are supplied to said distillation column as



- 36 -

a liquid feed thereto;

(9) said vapors thereby recovered are directed into heat exchange relation with said gaseous first stream thereby to heat said vapors and supply said cooling a step (b), whereupon said heated vapors are thereafter discharged as said volatile residue gas

5 fraction; and

(10) the quantities and temperatures of said feed streams to said contacting device and said distillation column are effective to maintain the overhead temperatures of said contacting device and said distillation column at temperatures whereby the major portions of the components in said relatively less volatile fraction are

10 recovered.

5. A process for the separation of a gas stream containing methane, C₂ components, C₃ components and heavier hydrocarbon components into a volatile residue gas fraction and a relatively less volatile fraction containing said C₂ components, C₃ components and
15 heavier hydrocarbon components or said C₃ components and heavier hydrocarbon components, which process comprises

(g) cooling said gas stream under pressure sufficient to partially condense it and separating to provide a vapor stream and a condensed stream;

(h) dividing said vapor stream into gaseous first and second streams;

20 (i) cooling said gaseous first stream under pressure to condense substantially all of it and thereafter allowing it to expand to a lower pressure whereby it is further cooled;

(j) allowing said gaseous second stream to expand to said lower pressure;

(k) allowing said condensed stream to expand to said lower pressure; and

(l) fractionating said cooled expanded first stream, said expanded second stream,
25 and said expanded condensed stream and said lower pressure whereby the components of said relatively less volatile fraction are recovered;

characterised in that

(6) said expanded cooled first stream is directed into heat exchange relation with a warmer distillation stream which rises from fractionation stages of a distillation
30 column, thereby cooling said distillation stream sufficiently to at least partially condense it;

(7) at least a portion of said expanded second stream is intimately contacted



- 37 -

with at least a portion of said at least partially condensed distillation stream in a contacting device containing at least a fractional theoretical separation stage, and thereafter the vapors and liquids from said contacting device are separated;

(8) said liquids thereby recovered are supplied to said distillation column as
5 a liquid feed thereto;

(9) said vapors thereby recovered are directed into heat exchange relation with said gaseous first stream thereby to heat said vapors and supply said cooling of step (c), whereupon said heated vapors are thereafter discharged as said volatile residue gas fraction; and

10 (10) the quantities and temperatures of said feed streams to said contacting device and said distillation column are effective to maintain the overhead temperatures of said contacting device and said distillation column at temperatures whereby the major portions of the components in said relatively less volatile fraction are recovered.

15 6. A process for the separation of a gas stream containing methane, C₂ components, C₃ components and heavier hydrocarbon components into a volatile residue gas fraction and a relatively less volatile fraction containing said C₂ components, C₃ components and heavier hydrocarbon components or said C₃ components and heavier hydrocarbon components, which process comprises
20 components, which process comprises

(g) cooling said gas stream under pressure sufficiently to partially condense it and separating to provide a vapor stream and a condensed stream;

(h) dividing said vapor stream into gaseous first and second streams;

(i) combining said gaseous first stream with at least a portion of said condensed
25 stream to form a combined stream;

(j) cooling said combined stream under pressure to condense substantially all of it and allowing it to thereafter expand to a lower pressure whereby it is further cooled;

(k) allowing said gaseous second stream to expand to said lower pressure; and

(l) fractionating said cooled expanded combined stream, said expanded second
30 stream, and any remaining portion of said condensed stream at said lower pressure whereby the components of said relatively less volatile fraction are recovered;



characterised in that

(6) said expanded cooled combined stream is directed into heat exchange relation with a warmer distillation stream which rises from fractionation stages of a distillation column, thereby cooling said distillation stream sufficiently to at least partially
5 condense it;

(7) at least a portion of said expanded second stream is intimately contacted with at least a portion of said at least partially condensed distillation stream in a contacting device containing at least a fractional theoretical separation stage, and thereafter the vapors and liquids from said contacting device are separated;

10 (8) said liquids thereby recovered are supplied to said distillation column as a liquid feed thereto;

(9) said vapors thereby recovered are directed into heat exchange relation with said combined stream thereby to heat said vapors and supply said cooling of step (d), whereupon said heated vapors are thereafter discharged as said volatile residue gas
15 fraction; and

(10) the quantities and temperatures of said feed streams to said contacting device and said distillation column are effective to maintain the overhead temperatures of said contacting device and said distillation column at temperatures whereby the major portions of the components in said relatively less volatile fraction are
20 recovered.

7. A process according to any one of claims 1 to 6, wherein at least a portion of said liquids separated from said contacting device are heated before being supplied to said distillation column as a feed thereto.

25 8. A process according to any one of claims 1 to 5, wherein

(a) vapor is separated from said at least partially condensed distillation stream before entering said contacting device, forming a residual vapor stream; and

(b) said residual vapor stream is combined with said vapors separated from said contacting device to form said volatile residue gas fraction, whereupon said volatile residue gas fraction is directed into heat exchange relation with said gaseous first stream thereby to heat said volatile residue gas fraction and supply said cooling of said gaseous



first stream.

9. A process according to claim 6 wherein

(a) vapor is separated from said at least partially condensed distillation stream
5 before entering said contacting device, forming a residual vapor stream; and

(b) said residual vapor stream is combined with said vapors separated from said
contacting device to form said volatile residue gas fraction, whereupon said volatile
residue gas fraction is directed into heat exchange relation with said combined stream
thereby to heat said volatile residue gas fraction and supply said cooling of said combined
10 stream.

10. An apparatus for the separation of a gas stream containing methane, C₂
components, C₃ components and heavier hydrocarbon components into a volatile residue
gas fraction and a relatively less volatile fraction containing said C₂ components, C₃
15 components and heavier hydrocarbon components or said C₃ components and heavier
hydrocarbon components said apparatus comprising

(a) a dividing means to divide said gas stream into gaseous first and second
streams;

(b) a first heat exchange means connected to said dividing means to receive said
20 gaseous first stream and to cool it under pressure sufficiently to substantially condense it;

(c) a first expansion means connected to said first heat exchange means to receive
said substantially condensed first stream and to expand it to a lower pressure, whereby said
stream is further cooled;

(d) a cooling means connected to said dividing means to receive said gaseous
25 second stream and to cool it under pressure;

(e) a second expansion means connected to said cooling means to receive said
cooled second stream and to expand it to said lower pressure; and

(f) a fractionation tower connected to said first expansion means and said second
expansion means to receive said expanded streams therefrom;

30 characterised in that said apparatus further comprises

(1) a second heat exchange means connected to said first expansion means



to receive said expanded cooled first stream, said second heat exchange means being further connected to said fractionation tower to receive a warmer distillation stream which rises from fractionation stages of a distillation column in said fractionation tower, thereby cooling said distillation stream sufficiently to at least partially condense it;

- 5 (2) a contacting and separating means connected to receive at least a portion of said at least partially condensed distillation stream and at least a portion of said cooled expanded second stream wherein said streams are commingled in at least one contacting device, said contacting and separating means including separating means to separate the vapor and liquid after contact in said contacting device to form a vapor stream and a liquid
- 10 stream, said contacting and separating means being further connected to supply said liquid stream to said distillation column in said fractionation tower as a liquid feed thereto, said contacting and separating means being further connected to supply said vapor stream to said first heat exchange means to heat said vapor stream and thereby supply the cooling of step (b), whereupon said heated vapor stream is thereafter discharged as said volatile
- 15 residue gas fraction; and

- (3) control means adapted to regulate the quantities and temperatures of said feed streams to said contacting and separating means and said fractionation tower to maintain the overhead temperatures of said contacting and separating means and said fractionation tower at temperatures whereby the major portions of the components in said
- 20 relatively less volatile fraction are recovered.

11. An apparatus for the separation of a gas stream containing methane, C₂ components, C₃ components and heavier hydrocarbon components into a volatile residue gas fraction and a relatively less volatile fraction containing said C₂ components, C₃
- 25 components and heavier hydrocarbon components or said C₃ components and heavier hydrocarbon components, said apparatus comprising

- (a) a cooling means to cool said gas stream under pressure;
- (b) a dividing means connected to said cooling means to receive said cooled gas stream and to divide it into gaseous first and second streams;
- (c) a first heat exchange means connected to said dividing means to receive said gaseous first stream and to cool it under pressure sufficiently to substantially condense it;

30



- 41 -

(d) a first expansion means connected to said first heat exchange means to receive said substantially condensed first stream and to expand it to a lower pressure, whereby said stream is further cooled;

(e) a second expansion means connected to said dividing means to receive said
5 gaseous second stream and to expand it to said lower pressure; and

(f) a fractionation tower connected to said first expansion means and said second expansion means to receive said expanded streams therefrom;

characterised in that said apparatus further comprises

(1) a second heat exchange means connected to said first expansion means
10 to receive said expanded cooled first stream, said second heat exchange means being further connected to said fractionation tower to receive a warmer distillation stream which rises from fractionation stages of a distillation column in said fractionation tower, thereby cooling said distillation stream sufficiently to at least partially condense it;

(2) a contacting and separating means connected to receive at least a portion
15 of said at least partially condensed distillation stream and at least a portion of said expanded second stream wherein said streams are commingled in at least one contacting device, said contacting and separating means including separating means to separate the vapor and liquid after contact in said contacting device to form a vapor stream and a liquid stream, said contacting and separating means being further connected to supply said liquid
20 stream to said distillation column in said fractionation tower as a liquid feed thereto, said contacting and separating means being further connected to supply said vapor stream to said first heat exchange means to heat said vapor stream and thereby supply the cooling of step (c), whereupon said heated vapor stream is thereafter discharged as said volatile residue gas fraction; and

25 (3) control means adapted to regulate the quantities and temperatures of said feed streams to said contacting and separating means and said fractionation tower to maintain the overhead temperatures of said contacting and separating means and said fractionation tower at temperatures whereby the major portions of the components in said relatively less volatile fraction are recovered.



12. An apparatus for the separation of a gas stream containing methane, C₂ components, C₃ components and heavier hydrocarbon components into a volatile residue gas fraction and a relatively less volatile fraction containing said C₂ components, C₃ components and heavier hydrocarbon components or said C₃ components and heavier hydrocarbon components, said apparatus comprising

(a) a dividing means to divide said gas stream into gaseous first and second streams;

(b) a first heat exchange means connected to said dividing means to receive said gaseous first stream and to cool it under pressure sufficiently to substantially condense it;

(c) a first expansion means connected to said first heat exchange means to receive said substantially condensed first stream and to expand it to a lower pressure, whereby said stream is further cooled;

(d) a cooling means connected to said dividing means to receive said gaseous second stream and to cool it under pressure sufficiently to partially condense it;

(e) a separation means connected to said cooling means to receive said cooled second stream and separate it thereby to provide a first vapor stream and a condensed stream;

(f) a second expansion means connected to said separation means to receive said first vapor stream and to expand it to said lower pressure;

(g) a third expansion means connected to said separation means to receive said condensed stream and to expand it to said lower pressure; and

(h) a fractionation tower connected to said first expansion means, said second expansion means, and said third expansion means to receive said expanded streams therefrom;

characterised in that said apparatus further comprises

(1) a second heat exchange means connected to said first expansion means to receive said expanded cooled first stream, said second heat exchange means being further connected to said fractionation tower to receive a warmer distillation stream which rises from fractionation stages of a distillation column in said fractionation tower, thereby cooling said distillation stream sufficiently to at least partially condense it;



(2) a contacting and separating means connected to receive at least a portion of said at least partially condensed distillation stream and at least a portion of said expanded first vapor stream wherein said streams are commingled in at least one contacting device, said contacting and separating means including separating means to
 5 separate the vapor and liquid after contact in said contacting device to form a second vapor stream and a liquid stream, said contacting and separating means being further connected to supply said liquid stream to said distillation column in said fractionation tower as a liquid feed thereto, said contacting and separating means being further connected to supply said second vapor stream to said first heat exchange means to heat said second vapor
 10 stream and thereby supply the cooling of step (b), whereupon said heated second vapor stream is thereafter discharged as said volatile residue gas fraction; and

(3) control means adapted to regulate the quantities and temperatures of said feed streams to said contacting and separating means and said fractionation tower to maintain the overhead temperatures of said contacting and separating means and said
 15 fractionation tower at temperatures whereby the major portions of the components in said relatively less volatile fraction are recovered.

13. An apparatus for the separation of a gas stream containing methane, C_2 components, C_3 components and heavier hydrocarbon components into a volatile residue
 20 gas fraction and a relatively less volatile fraction containing said C_2 components, C_3 components and heavier hydrocarbon components or said C_3 components and heavier hydrocarbon components, said apparatus comprising

- (a) a first cooling means to cool said gas stream under pressure;
- (b) a dividing means connected to first cooling means to receive said cooled gas
 25 stream and to divide it into gaseous first and second streams;
- (c) a first heat exchange means connected to said dividing means to receive said gaseous first stream and to cool it under pressure sufficiently to substantially condense it;
- (d) a first expansion means connected to said first heat exchange means to receive said substantially condensed first stream and to expand it to a lower pressure, whereby said
 30 stream is further cooled;
- (e) a second cooling means connected to said dividing means to receive said



- 44 -

gaseous second stream and to cool it under pressure sufficiently to partially condense it;

(f) a separation means connected to said second cooling means to receive said cooled second stream and separate it thereby to provide a first vapor stream and a condensed stream;

5 (g) a second expansion means connected to said separation means to receive said first vapor stream and to expand it to said lower pressure;

(h) a third expansion means connected to said separation means to receive said condensed stream and to expand it to said lower pressure; and

(i) a fractionation tower connected to said first expansion means, said second
10 expansion means, and said third expansion means to receive said expanded streams therefrom;

characterised in that said apparatus further comprises

(1) a second heat exchange means connected to said first expansion means
to receive said expanded cooled first stream, said second heat exchange means being
15 further connected to said fractionation tower to receive a warmer distillation stream which rises from fractionation stages of a distillation column in said fractionation tower, thereby cooling said distillation stream sufficiently to at least partially condense it;

(2) a contacting and separating means connected to receive at least a portion
of said at least partially condensed distillation stream and at least a portion of said
20 expanded first vapor stream wherein said streams are commingled in at least one contacting device, said contacting and separating means including separating means to separate the vapor and liquid after contact in said contacting in said contacting device to form a second vapor and a liquid stream, said contacting and separating means being further connected to supply said liquid stream to said distillation column in said
25 fractionation tower as a liquid feed thereto, said contacting and separating means being further connected to supply said second vapor stream to said first heat exchange means to heat said second vapor stream and thereby supply the cooling of step (c), whereupon said heated second vapor stream is thereafter discharged as said volatile residue gas fraction; and

30 (3) control means adapted to regulate the quantities and temperatures of said feed streams to said contacting and separating means and said fractionation tower to



- 45 -

maintain the overhead temperatures of said contacting and separating means and said fractionation tower at temperatures whereby the major portions of the components in said relatively less volatile fraction are recovered.

5 14. An apparatus for the separation of a gas stream containing methane, C₂ components, C₃ components and heavier hydrocarbon components into a volatile residue gas fraction and a relatively less volatile fraction containing said C₂ components, C₃ components and heavier hydrocarbon components or said C₃ components and heavier hydrocarbon components, said apparatus comprising

10 (a) a cooling means to cool said gas stream under pressure sufficiently to partially condense it;

(b) a separation means connected to said cooling means to receive said cooled gas stream and separate it thereby to provide a first vapor stream and a condensed stream;

15 (c) a dividing means connected to said separation means to receive said first vapor stream and to divide it into gaseous first and second streams;

(d) a first heat exchange means connected to said dividing means to receive said gaseous first stream and to cool it under pressure sufficiently to substantially condense it;

20 (e) a first expansion means connected to said first heat exchange means to receive said substantially condensed first stream and to expand it to a lower pressure, whereby said stream is further cooled;

(f) a second expansion means connected to said dividing means to receive said gaseous second stream and to expand it to said lower pressure;

(g) a third expansion means connected to said separation means to receive said condensed stream and to expand it to said lower pressure; and

25 (h) a fractionation tower connected to said first expansion means, said second expansion means, and said third expansion means to receive said expanded streams therefrom;

characterised in that said apparatus further comprises

30 (1) a second heat exchange means connected to said first expansion means to receive said expanded cooled first stream, said second heat exchange means being further connected to said fractionation tower to receive a warmer distillation stream which



rises from fractionation stages of a distillation column in said fractionation tower, thereby cooling said distillation stream sufficiently to at least partially condense it;

(2) a contacting and separating means connected to receive at least a portion of said at least partially condensed distillation stream and at least a portion of said expanded second stream wherein said streams are commingled in at least one contacting device, said contacting and separating means including separating means to separate the vapor and liquid after contact in said contacting device to form a second vapor stream and a liquid stream, said contacting and separating means being further connected to supply said liquid stream to said distillation column in said fractionation tower as a liquid feed thereto, said contacting and separating means being further connected to supply said second vapor stream to said first heat exchange means to heat said second vapor stream and thereby supply the cooling of step (d), whereupon said heated second vapor stream is thereafter discharged as said volatile residue gas fraction; and

(4) control means adapted to regulate the quantities and temperatures of said feed streams to said contacting and separating means and said fractionation tower to maintain the overhead temperatures of said contacting and separating means and said fractionation tower at temperatures whereby the major portions of the components in said relatively less volatile fraction are recovered.

15. An apparatus for the separation of a gas stream containing methane, C_2 components, C_3 components and heavier hydrocarbon components into a volatile residue gas fraction and a relatively less volatile fraction containing said C_2 components, C_3 components and heavier hydrocarbon components or said C_3 components and heavier hydrocarbon components, said apparatus comprising

(a) a cooling means to cool said gas stream under pressure sufficiently to partially condense it;

(b) a separation means connected to said cooling means to receive said cooled gas stream and separate it thereby to provide a first vapor stream and a condensed stream;

(c) a dividing means connected to said separation means to receive said first vapor stream and to divide it into gaseous first and second streams;

(d) a combining means connected to combine said gaseous first stream and at least



- 47 -

a portion of said condensed stream into a combined stream;

(e) a first heat exchange means connected to said combining means to receive said combined stream and to cool it under pressure sufficiently to substantially condense it;

(f) a first expansion means connected to said first heat exchange means to receive
5 said substantially condensed combined stream and to expand it to a lower pressure, whereby said stream is further cooled;

(g) a second expansion means connected to said dividing means to receive said gaseous second stream and to expand it to said lower pressure;

(h) a third expansion means connected to said separation means to receive any
10 remaining portion of said condensed stream and to expand it to said lower pressure; and

(i) a fractionation tower connected to said first expansion means, said second expansion means, and said third expansion means to receive said expanded streams therefrom;

characterised in that said apparatus further comprises

15

(1) a second heat exchange means connected to said first expansion means to receive said expanded cooled combined stream, said second heat exchange means being further connected to said fractionation tower to receive a warmer distillation stream which rises from fractionation stages of a distillation column in said fractionation tower, thereby cooling said distillation stream sufficiently to at least partially condense it;

20

(2) a contacting and separating means connected to receive at least a portion of said at least partially condensed distillation stream and at least a portion of said expanded second stream wherein said streams are commingled in at least one contacting device, said contacting and separating means including separating means to separate the vapor and liquid after contact in said contacting device to form a second vapor stream and
25 a liquid stream, said contacting and separating means being further connected to supply said liquid stream to said distillation column in said fractionation tower as a liquid feed thereto, said contacting and separating means being further connected to supply said second vapor stream to said first heat exchange means to heat said second vapor stream and thereby supply the cooling of step (e), whereupon said heated second vapor stream is

30 thereafter discharged as said volatile residue gas fraction; and

(3) control means adapted to regulate the quantities and temperatures of



- 48 -

said feed streams to said contacting and separating means and said fractionation tower to maintain the overhead temperatures of said contacting and separating means and said fractionation tower at temperatures whereby the major portions of the components in said relatively less volatile fraction are recovered.

5

16. An apparatus according to any one of claims 10 to 15 which comprises a heating means connected to said contacting and separating means to receive at least a portion of said liquid stream separated therefrom and heat it, said heating means being further connected to supply said heated stream to said distillation column in said fractionation tower as a feed thereto.

10

17. An apparatus according to claim 10 or 11 which comprises

(a) a separation means connected to said second heat exchange means to receive said at least partially condensed distillation stream and separate it thereby to form a residual vapor stream and a liquid reflux stream, said separation means being further connected to supply said liquid reflux stream to said contacting and separating means; and

15

(b) a combining means connected to said separation means to receive said residual vapor stream, said combining means being further connected to said contacting and separating means to receive said vapor stream separated therefrom and combine it with said residual vapor stream to form said volatile residue gas fraction, said combining means being further connected to supply said volatile residue gas fraction to said first heat exchange means, thereby heating said volatile residue gas fraction and supplying said cooling of said gaseous first stream.

20

18. An apparatus according to any one of claims 12 to 14 which comprises

(a) a second separation means connected to said second heat exchange means to receive said at least partially condensed distillation stream and separate it thereby to form a residual vapor stream and a liquid reflux stream, said second separation means being further connected to supply said liquid reflux stream to said contacting and separating means; and

25

(b) a combining means connected to said second separation means to receive said



- 49 -

residual vapor stream, said combining means being further connected to said contacting and separating means to receive said second vapor stream separated therefrom and combine it with said residual vapor stream to form said volatile residue gas fraction, said combining means being further connected to supply said volatile residue gas fraction to
5 said first heat exchange means, thereby heating said volatile residue gas fraction and supplying said cooling of said gaseous first stream.

19. An apparatus according to claim 15 which comprises

(a) a second separation means connected to said second heat exchange means
10 to receive said at least partially condensed distillation stream and separate it thereby to form a residual vapor stream and a liquid reflux stream, said second separation means being further connected to supply said liquid reflux stream to said contacting and separating means; and

(b) a combining means connected to said second separation means to receive
15 said residual vapor stream, said combining means being further connected to said contacting and separating means to receive said second vapor stream separated therefrom and combine it with said residual vapor stream to form said volatile residue gas fraction, said combining means being further connected to supply said volatile residue gas fraction to said first heat exchange means, thereby heating said volatile residue gas fraction and
20 supplying said cooling of said combined stream.

20. A process according to claim 1 and substantially as hereinbefore described.

21. A process according to claim 2 and substantially as hereinbefore described.

22. A process according to claim 3 and substantially as hereinbefore described.

25 23. A process according to claim 4 and substantially as hereinbefore described.

24. A process according to claim 5 and substantially as hereinbefore described.

25. A process according to claim 6 and substantially as hereinbefore described.

26. An apparatus according to claim 10 and substantially as hereinbefore described.

27. An apparatus according to claim 11 and substantially as hereinbefore described.

30 28. An apparatus according to claim 12 and substantially as hereinbefore described.

29. An apparatus according to claim 13 and substantially as hereinbefore described.



- 50 -

30. An apparatus according to claim 14 and substantially as hereinbefore described.
31. An apparatus according to claim 15 and substantially as hereinbefore described.

DATED this 13th day of February, 2001

5

Elcor Corporation
by DAVIES COLLISON CAVE
Patent Attorneys for the Applicant(s)

2001
FEB 13







FIG. 1
(PRIOR ART)






FIG. 3




FIG. 4




FIG. 5

+




FIG. 6

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.